

# Declaration of Performance

**Nr.: 15651-0552-3-UK**

1. Unique identification of product type:  
**EN 15651-1: F-INT-EXT CC (Class 25LM)**
2. Identification of construction product:  
**Danaseal Contractor PF 552**  
**Batch number: See product packaging**
3. Intended use of product:  
**Sealant for use in facade elements**  
**Type F-INT-EXT CC (Class 25LM).**
4. Address and name of the producer:  
**Dana Lim A/S, Københavnsvej 220, 4600 Køge, Danmark**
5. Name and address of authorized representative:  
**Not relevant**
6. System and verification of consistency of the construction product (Annex V):  
**System 3 + 3**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**The notified body Fundacion Research & Innovation Tecnalia (1292)**  
**performed the testing of reaction to fire under system 3 and issued a test report**
8. In case of declaration of performance concerning a construction product covered by a European Technical Assessment has been issued:  
**Not relevant**



9. Declared Performance:  
 Conditioning: Method B  
 Substrate: Anodised aluminium (no primer)

Essential characteristic	Performance	Harmonized technical specification
Reaction to fire	E	EN 15651-1:2012
Release of chemicals dangerous to health and environment	Evaluated	
<b>Water and air thightness</b>		
a) Resisistance to flow	≤ 3 mm	
b) Loss of volume	≤ 10 %	
c) Tensile properties at maintained extension after water immersion	NF	
d) Tensile properties at maintained extension	NF	
e) Tensile properties at maintained extension; - 30°C	NF	
f) Tensile properties (secant modulus)	< 0,4 MPa	
g) Tensile properties (secant modulus; - 30°C)	< 0,9 MPa	
h) Adhesion/cohesion properties at maintained extension after 28 days water immersion	NF	
i) Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	NF	
j) Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Køge, 11.02.2021



Kenneth Holm Andersen  
 R&D Manager Sealing & Bonding

