

**Product Information:**

# Quattro Adhesive 213

**Premixed adhesive for walls**

**General description and typical applications:**

Quattro Adhesive 213 is a premixed water-based adhesive for mounting paper, glass felt, vinyl and easy-up wallpapers and lighter fiber glass web.

The glue is suitable for spray application and automatic application machines.

Quattro Adhesive 213 has increased strength with EVA-copolymer dispersion.

Quattro Adhesive 213 meets the strict environmental and indoor air quality requirements required for the **NORDIC ECOLABEL and M1 certifications**



5097-0012



**Physical / chemical properties:**

**Adhesive:**

Type: Modified starch with EVA-copolymer dispersion  
 Colour: White  
 Consistency: Creamy, thixotropic  
 Solids content: approx. 14 %  
 Shelf life: Approx. 12 months in tightly closed packing if stored cool.  
 The product should be protected from frost.

**Packaging:**

Item no.	Size
46421	5 kg
46422	15 kg



## Directions for use:

- Preparation:** *The foundation must be clean, dry, solid, non-smudging and free from wallpaper remnants.*
- Non-absorbent and painted foundations are sanded and washed with a cleaning agent. Necessary priming of plaster can be done with diluted glue.*
- On smudging or very absorbent surfaces priming should be done with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Dilution:** *Stir before use. If necessary, it can be diluted with water.*
- Application temperature:** *18 °C to 30 °C.*
- Application:** **glass felt /fiber glass web /easy-up wallpaper:**  
*When glass felt, fiber glass web and wallpaper types which recommended that adhesive is applied on the wall (easy- up wallpaper), adhesive can be applied by brush, roller or airless spray equipment.*
- Ordinary Wallpaper:**  
*The adhesive is applied in an even layer on the backside of the wallpaper, where should soften the wallpaper before hanging. Avoid adhesive on the front side of the paper. Adhesive on the front side of the paper can be difficult to remove. Any glue on the front should be carefully removed with a damp sponge / cloth.*
- The glue is suitable for automatic application machines.*
- For mounting instructions, please see the instructions from the manufacturer of the material.*
- Yield:** *3-5 m<sup>2</sup> pr. kg*
- Painting:** *After complete drying of the adhesive, the wallpaper, felt and web can be painted.*
- Cleaning:** *Uncured adhesive spots can be removed with a damp cloth. Clean tools with water.*

**For further information concerning safety, refer to Safety Datasheet.**

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK**

**PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**