

Product Information:

Wallpaper Adhesive 209

Ready mixed adhesive for wallpaper

General description and application:

Wallpaper Adhesive 209 is a ready mixed adhesive for wallpaper mounting in dry and heated rooms.

The glue is suitable for spray application and automatic application machines.

Wallpaper Adhesive 209 has increased strength with EVA-copolymer dispersion.

The product has been tested and approved as a product with low emission according to the M1-classification.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.



Physical / chemical properties:

Adhesive:

Type: Modified starch with EVA-copolymer dispersion
 Colour: White
 Consistency: Creamy, thixotropic
 Solids content: approx. 14 %
 Density: approx. 1.0 kg/L
 Shelf life: Approx. 12 months in tightly closed packing if stored cool.
 The product should be protected from frost.

Packaging:

Item no.	Size
8722	5 L
8723	15 L



Directions for use:

- Preparation:** *The foundation must be clean, dry, solid, and free from wallpaper remnants.*
- Non-absorbent and painted foundations are sanded and washed with a cleaning agent. Necessary priming of plaster can be done with diluted glue.*
- On smudging or very absorbent surfaces priming should be done with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Dilution:** *Stir before use. If necessary, it can be diluted with water.*
- Application temperature:** *18 °C to 25 °C.*
- Application:** *The adhesive is applied in an even layer on the backside of the wallpaper, where it should soften the wallpaper before setup. Avoid adhesive on the front side of the paper.*
- Adhesive on the front side of the paper can be difficult to remove. Any glue on the front should be carefully removed with a damp sponge / cloth.*
- The glue is suitable for automatic application machines.*
- When wallpaper types which recommended that adhesive is applied on the wall (easy- up wallpaper) used, adhesive can be applied by brush, roller or airless spray equipment.*
- Range of coverage:** *3-5 m² pr. liter*
- Painting:** *After complete drying of the adhesive, the wallpaper can be painted.*
- Also refer to the instructions from the wallpaper supplier.**
- Cleaning:** *Wash hands and skin with soap and water.*
Adhesive stains and spots are removed immediately with a damp cloth.
Tools are cleaned with lukewarm water.
Hardened adhesive is removed mechanically or dissolved by soaking in water.

Health and safety:

For further information on safety, refer to safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75