

Product Information:

Fibre Glass Web Adhesive 212

Ready-mixed adhesive for fibre glass web

General description and application:

Fibre Glass Web Adhesive 212 is water-based adhesive, developed for mounting glass fibre web and glass felt in dry and heated rooms.

The adhesive is easy to apply with either roller or brush.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.



Physical / chemical properties:

Adhesive:

- Type: Modified starch/PVAc-dispersion
- Colour: White
- Consistency: Creamy, thixotropic
- Solids content: approx. 17 %
- Density: approx. 1 Kg/L
- Shelf life: Minimum 12 months in tightly closed packing if stored dry and cool.
The product should be protected from frost.

Packaging:

Item no.	Size
46321	5 kg square
46341	15 kg square



Directions for use:

- Preparation:** *The foundation must be clean, dry, solid, non-smudging and free from wall-paper remnants.*
- Non-absorbent and painted foundations are sanded and washed with a cleaning agent.*
- On smudging or very absorbent surfaces priming should be done with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Dilution:** *The adhesive is stirred before use. If necessary, it can be diluted with water.*
- Application temperature:** *15 °C – 30 °C, best at room temperature.*
- Application:** *The adhesive is applied to the wall in an even layer with a brush or roller. Do not apply more adhesive, than materials can be mounted while the adhesive is still wet.*
- Always avoid adhesive on the front side of material. Any glue on the front should be carefully removed with a damp sponge / cloth.*
- Range of coverage:** *3 - 5 m²/ ltr.*
- Drying time:** *Normally approx. 24 hours, depending on room temperature and humidity.*
- Treatment:** *Woven fibre glass fabrics can be painted when the adhesive is completely dry.*
- Always follow the instructions of the material suppliers.**
- Cleaning:** *Wash hands and skin with soap and water.*
Adhesive stains and spots are removed immediately with a damp cloth.
Tools are cleaned with lukewarm water.
Hardened adhesive is removed mechanically or dissolved by soaking in water.

Health and safety:

For further information on safety, refer to safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75