

Product Information:

Stucco Adhesive 296

Water based adhesive for stucco and rosettes

General description and application:

Stucco Adhesive 296 is a water based combined adhesive and filler, making it possible to bond and finish stucco and rosettes of polyurethane (PU) and polystyrene (PS).

The stucco adhesive can be sanded and painted.



Physical / chemical properties:

Adhesive:

- Type: Water based acrylic adhesive and filler
- Colour: White
- Consistency: Tixotropic
- Shelf life: Minimum 12 months in tightly closed packing if stored cool. Protect from freezing.
- Packaging:

Item no	Size
29632	300 ml cartridge

Cured adhesive:

- Paintable: Yes
- Resistance: Temperature: Approx. -25 °C to +80 °C.
- Water: Resistant to moisture but not constant water.



Directions for use:

Preparation:

The ceiling and walls must be firm, even and clean, free from dust and loose particles. Old wallpaper or paint must be removed. Uneven surfaces must be filled. The stucco should be mounted before final painting or paperhanging.

It is advised to draw a line on the wall, corresponding to the high of the stucco.

The mounting should be started in the least visible corner, as the pattern of the stucco rarely fits completely.

Application:

When the stucco has been fitted, the adhesive is applied to the stucco backsides as well as on one end. The stucco is placed correctly according to the line, and pressed firmly against the wall and ceiling. In some cases, it might be necessary to support the stucco with small nails.

When the stucco has been mounted, the joints between ceiling and wall, and the joints between the stucco elements are filled with the stucco adhesive. Surplus adhesive is removed with a moist sponge before curing

When mounting rosettes the stucco adhesive is applied to the backside of the rosette, in lines with 5 – 10 cm distance. The rosette is then pressed firmly against the ceiling or wall.

It is always recommended to follow the instructions of the stucco supplier

Yield:

40 – 80 ml/meter, depending on size of stucco / rosettes.

Treatment:

After curing, the Stucco Adhesive 296 can be painted.

Cleaning:

Tools are cleaned – and adhesive removed with warm water. Hands are washed with water and soap.

Health and safety:

For further information on safety, please refer to product safety datasheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK

PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75