

SAFETY DATA SHEET

Wood Glue D4 Outdoor 440

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Wood Glue D4 Outdoor 440

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Wood glue

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Dana Lim A/S

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

Contact person

Product Safety Department

E-mail

info@danalim.dk

Revision

29/12/2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Safety statement(s)

General

-

Prevention

-

Response

-

Storage

-

Disposal

-

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Hazardous substances

None known.

Additional labelling

EUH208, Contains Formaldehyde, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210, Safety data sheet available on request.

Active substance(s):

Formaldehyde (0.0549 g/100g)

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (0.0011 g/100g)

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propylene carbonate	CAS No.: 108-32-7 EC No.: 203-572-1 UK-REACH: Index No.: 607-194-00-1	3-5%	Eye Irrit. 2, H319	
vinyl acetate	CAS No.: 108-05-4 EC No.: 203-545-4 UK-REACH: Index No.: 607-023-00-0	<0.1%	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT SE 3, H335 Carc. 2, H351	[1]
Formaldehyde	CAS No.: 50-00-0 EC No.: 200-001-8 UK-REACH: Index No.: 605-001-00-5	<0.1%	Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 (SCL: 25.00 %) Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 (SCL: 0.20 %) Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 3, H331 STOT SE 3, H335 (SCL: 5.00 %) Muta. 2, H341 Carc. 1B, H350	[1]
Methanol	CAS No.: 67-56-1 EC No.: 200-659-6 UK-REACH: Index No.: 603-001-00-X	<0.05%	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 STOT SE 2, H371 (SCL: 3.00 %)	[1], [3]
dodecylguanidine monohydrochloride	CAS No.: 13590-97-1 EC No.: 237-030-0 UK-REACH: Index No.:	<0.05%	Acute Tox. 4, H302 Skin Corr. 1B, H314 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 911-418-6 UK-REACH: Index No.:	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 Acute Tox. 2, H330	

Aquatic Acute 1, H400 (M=100)
Aquatic Chronic 1, H410 (M=100)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

vinyl acetate

Long term exposure limit (8 hours) (ppm): 5

Long term exposure limit (8 hours) (mg/m³): 17,6

Short term exposure limit (15 minutes) (ppm): 10

Short term exposure limit (15 minutes) (mg/m³): 35,2

Formaldehyde

Long term exposure limit (8 hours) (ppm): 2

Long term exposure limit (8 hours) (mg/m³): 2,5

Short term exposure limit (15 minutes) (ppm): 2

Short term exposure limit (15 minutes) (mg/m³): 2,5

Methanol

Long term exposure limit (8 hours) (ppm): 200

Long term exposure limit (8 hours) (mg/m³): 266

Short term exposure limit (15 minutes) (ppm): 250

Short term exposure limit (15 minutes) (mg/m³): 333

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

propylene carbonate

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	10 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	20 mg/kg bw/day
Long term – Local effects - General population	Inhalation	10 mg/m ³

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Local effects - Workers	Inhalation	20 mg/m ³
Long term – Systemic effects - General population	Inhalation	17,4 mg/m ³
Long term – Systemic effects - Workers	Inhalation	70,5 mg/m ³
Long term – Systemic effects - General population	Oral	10 mg/kg bw/day

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration	Route of exposure	DNEL
Long term – Local effects - General population	Inhalation	20 µg/m ³
Long term – Local effects - Workers	Inhalation	20 µg/m ³
Short term – Local effects - General population	Inhalation	40 µg/m ³
Short term – Local effects - Workers	Inhalation	40 µg/m ³
Long term – Systemic effects - General population	Oral	90 µg/kgbw/day
Short term – Systemic effects - General population	Oral	110 µg/kgbw/day

vinyl acetate

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	420 µg/kgbw/day
Long term – Local effects - Workers	Inhalation	17.6 mg/m ³
Long term – Systemic effects - Workers	Inhalation	17.6 mg/m ³
Short term – Local effects - Workers	Inhalation	35.2 mg/m ³
Short term – Systemic effects - Workers	Inhalation	35.2 mg/m ³

PNEC

propylene carbonate

Route of exposure	Duration of Exposure	PNEC
Activated Sludge Plant		7400 mg/L
Freshwater		0,9 mg/L
Intermittent release		9 mg/L
Marine water		0,09 mg/L
Soil		0,81 mg/kg

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Duration of Exposure	PNEC
Freshwater		3.39 µg/L
Freshwater sediment		27 µg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L
Soil		10 µg/kg

vinyl acetate

Route of exposure	Duration of Exposure	PNEC
Freshwater		16 µg/L
Freshwater sediment		67 µg/kg
Intermittent release (freshwater)		126 µg/L
Marine water		1.6 µg/L
Marine water sediment		6.7 µg/kg
Sewage treatment plant		6 mg/L

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Soil

3.5 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

8.3. Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

No specific requirements.

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388



Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

White

Odour / Odour threshold

Faint

pH

4,5-5,5

Density (g/cm³)

1.06

Kinematic viscosity

14000-22000 mPa.s (20 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

Auto-Ignition (°C)

Testing not relevant or not possible due to the nature of the product.

Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	49,6-75 mg/kg ·
Other information	

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	0,33 mg/l, 4 h aerosol ·

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Other information

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	141 mg/kg
Other information	

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	OECD 406
Species	Guinea pig
Result	Adverse effect observed (sensitising)
Other information	

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

None known.

Other information

vinyl acetate has been classified by IARC as a group 2B carcinogen.

Formaldehyde has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	EC50
Result	0,027 mg/l
Other information	

12.2. Persistence and degradability

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Biodegradable	Yes
Test method	OECD 301 D
Result	>60%

12.3. Bioaccumulative potential

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Potential bioaccumulation No
LogPow No data available.
BCF 3.6
Other information

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

None known.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

None known.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Formaldehyde

Methanol

REACH, Annex XVII

Methanol is subject to restrictions, UK-REACH annex XVII (entry 69).

Additional information

Not applicable.

Sources

Control of Major Accident Hazards (COMAH) Regulations 2015.

In accordance with Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products as retained and amended in UK law.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H314, Corrosive to the respiratory tract.

H225, Highly flammable liquid and vapour.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H311, Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H331, Toxic if inhaled.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H341, Suspected of causing genetic defects.

H350, May cause cancer.

H351, Suspected of causing cancer.

H370, Causes damage to organs.

H371, May cause damage to organs.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en