

SAFETY DATA SHEET

Roof Sealant 559

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Roof Sealant 559

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Sealant

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Dana Lim A/S

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

Fax: +45 56 64 00 90

Contact person

Product Safety Department

E-mail

info@danalim.dk

SDS date

2021-08-11

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Flammable liquid and vapour. (H226)

May cause drowsiness or dizziness. (H336)

Safety statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Use only outdoors or in a well-ventilated area. (P271)

Response

-

Storage

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

n-butyl acetate

2.3. Other hazards

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated heavy paraffinic	CAS No.: 64742-54-7	25-40%	Asp. Tox. 1, H304	
	EC No.: 265-157-1			
	REACH: 01-2119484627-25-XXXX			
	Index No.: 649-467-00-8			
n-butyl acetate	CAS No.: 123-86-4	25-40%	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1]
	EC No.: 204-658-1			
	REACH:			
	Index No.: 607-025-00-1			
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	CAS No.: 52829-07-9	<1%	Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) Aquatic Chronic 2, H411 Repr. 2, H361f	
	EC No.: 258-207-9			
	REACH: 01-2119537297-32-XXXX			
	Index No.:			

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

No special

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
n-butyl acetate

Long term exposure limit (8 hours) (ppm): 150

Long term exposure limit (8 hours) (mg/m³): 724

Short term exposure limit (15 minutes) (ppm): 200

Short term exposure limit (15 minutes) (mg/m³): 966

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

No data available

PNEC

No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of

a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements

Individual protection measures, such as personal protective equipment


Generally

Use only CE marked protective equipment.



Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
If used in small and very badly ventilated rooms (not relevant if the room is well ventilated)	A	Class 2 (medium capacity)	Brown	EN14387	


Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.3	> 60	EN374-2, EN374-3, EN388	
When applying the sealant with a caulking gun and when finishing with a joint nail, work can be carried out without gloves if skin contact is avoided.				

Eye protection

Type	Standards	
Wear safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Paste

Colour

Various colours

Odour / Odour threshold

Solvent

pH

6,2

Density (g/cm³)

0.93

Kinematic viscosity

15000.00 mPa.s

Particle characteristics

Testing not relevant or not possible due to nature of the product.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

126.00 °C

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Relative vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

27.00 °C

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

1.20 - 7.50 v/v%

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	n-butyl acetate
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	10760-13100 mg/kg ·
Other information	

Product/substance	n-butyl acetate
Test method	
Species	Rat
Route of exposure	Dermal
Test	LD50
Result	14100 mg/kg ·
Other information	

Product/substance	n-butyl acetate
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	23,4 mg/l 4 hours ·
Other information	

Skin corrosion/irritation

Product/substance	n-butyl acetate
Test method	
Species	Rabbit
Duration	No data available.
Result	Adverse effect observed (Irritating)
Other information	

Serious eye damage/irritation

Product/substance	n-butyl acetate
Test method	
Species	Rabbit
Duration	No data available.
Result	Adverse effect observed (Irritating)
Other information	

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Long term effects

No special

Endocrine disrupting properties

No special

Other information

No special

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	n-butyl acetate
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	EC50
Result	44 mg/l ·
Other information	

Product/substance	n-butyl acetate
Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	EC50
Result	647,7 mg/l ·
Other information	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

Avoid discharge to lakes, streams, sewers, etc.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

UN- or ID number	UN proper shipping name	Labels	Packing group	Tunnel restriction code
-			-	-

IMDG

UN- or ID number	UN proper shipping name	Labels	Packing group	EmS
-			-	-, -

MARINE POLLUTANT

No

IATA

UN- or ID number	UN proper shipping name	Labels	Packing group
-			-

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

Additional information

Not applicable

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H318, Causes serious eye damage.

H336, May cause drowsiness or dizziness.

H361f, Suspected of damaging fertility.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWG = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en