

Product Information:

Backer Rod 983

Rectangular profile, open cells.**General description and application:**

Backer Rod 983 is used as backing material for plastic sealants for interior use, to ensure correct dimensions of the joints and as bond-breaker. Consequently, improved movement tolerance and extended durability of the joint are achieved.

Backer Rod 983 are rectangular profiles with open cells and can therefore only be recommended for interior applications.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.

**Physical / chemical properties:****Backer Rod:**

Type:

Polyethylene foam, rectangular profile, open cells

Colour:

Grey

Packaging:

Item no.	Size	Length
7715	20 x 30 mm	50 units á 2 m
7726	25 x 35 mm	50 units á 2 m
7723	20 x 40 mm	50 units á 2 m
7727	25 x 40 mm	50 units á 2 m



Directions for use:*Preparation:*

Choose correct backer rod size according to joint size and chosen sealant.

Backer Rod 983 can be used for plastic sealants.

Backer Rod 983 has open cells, and should therefore, only be used for interior joints.

The size of the backer rod should be approx. 25 % wider than the joint to fit tightly.

Application:

Backer Rod 983 should be inserted at correct depth according to joint size and chosen sealant. Refer to the Product information of the chosen sealant for further information.

Insert the backer rod to the joint with a blunt tool to avoid any damage of the rod during the installation.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**