

**Product Information:**

# Primer 960

**Primer for closed surfaces****General description and application:**

Primer 960 is a special developed adhesion promoter, that improves adhesion of MS-polymers, Polyurethan (PU) and siliconebased sealants on closed and non-porous surfaces e.g. glass, metal and most types of plastic.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.

**Physical / chemical properties:****Primer:**

Type: 1-component solvent containing primer.  
Colour: Light yellow  
Consistency: Liquid  
Specific gravity: approx. 0.8 kg/litre  
Shell life: Minimum 1 year in unopened packing, if stored cool and dry.  
Packing:

Art. no.	Size
7573	250 ml



**Directions for use:**

Preparation:	<p><i>All surfaces must be clean, dry, and free of grease, dust and loose particles.</i></p> <p><i>Surfaces must be degreased with e.g. acetone or ethanol before primer is applied. Metals are to be cleaned mechanically before degreasing.</i></p> <p><i>The choice of primer must be made after sufficient adhesion- and compatibility tests.</i></p>
Application:	<p><i>The primer is applied with a soft brush or cloth, in a thin even layer. Application should be made carefully, as the primer will be visible after drying. Use covering tape if necessary.</i></p>
Consumption:	<p><i>60 ml/m<sup>2</sup> adhesion surface.</i></p>
Drying time:	<p><i>10-20 minutes at 20 °C.</i></p> <p><i>Apply the sealant as soon as possible after the primer is completely dry, to avoid contamination of the primed surface.</i></p>
Cleaning:	<p><i>The brush can be cleaned with an organic solvent, e.g. acetone.</i></p>

**Health and safety:**

*For further information on safety, please refer to product safety data sheet.*

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DANMARK – INFO@DANALIM.DK**  
**TLF. 56 64 00 70 - TEKNISK SERVICE TLF. 56 64 00 75**