

Product Information:

Wallpaper Adhesive with PVAc 208

Premixed PVAc – reinforced adhesive for wallpaper

General description and application:

Wallpaper Adhesive 208 is ready mixed water- and PVAc reinforced starch-based adhesive for hanging of ordinary wallpaper in dry rooms.

The glue is suitable for automatic application machines.



Physical / chemical properties:

Adhesive:

- Type: *wheat starch-reinforced with polyvinyl acetate-dispersion*
- Colour: *Beige*
- Consistency: *Creamy, thixotropic*
- Solids content: *approx. 20 %*
- Shelf life: *Approx. 6 months in tightly closed packing if stored cool and dry. The product should be protected from frost.*

Packaging:

Item no.	Size
20815	15 kg



Directions for use:

- Preparation:** *The foundation must be clean, dry, solid, none smudging and free from wallpaper remnants.*
- The adhesive will during drying make a contraction of the wallpaper. This will make some tension in the wallpaper and result in a smooth surface. The tension means however that the surface must be strong. If the foundation is too weak, the wallpaper can pull the foundation apart.*
- On smudging or very absorbent surfaces priming should be done with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Non-absorbent and painted foundations are sanded and washed with a cleaning agent.*
- Dilution:** *Stir before use. If necessary, it can be diluted with water.*
- Application temperature:** *18 °C to 25 °C.*
- Application:** *The adhesive is applied in an even layer on the backside of the wallpaper, where it should soften the wallpaper before hanging. Avoid adhesive on the front side of the wallpaper. Any glue that comes to the front, removed depending on paper quality with a damp cloth or sponge.*
- Range of coverage:** *15 kg adhesive covers approx. 65 m².*
- Cleaning:** *Wash hands and skin with soap and water.
Adhesive stains and spots are removed immediately with a damp cloth.
Tools are cleaned with lukewarm water.
Hardened adhesive is removed mechanically or dissolved by soaking in water.*
- Also refer to the instructions from the wallpaper supplier.**

Health and Safety:

For further information on safety, refer to product safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**