

SAFETY DATA SHEET

Vådrumssilicone 512 transparent

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Vådrumssilicone 512 transparent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Sealing and filling

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Dana Lim A/S

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

Contact person

Product Safety Department

E-mail

info@danalim.dk

Revision

6/15/2023

SDS Version

1.0

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

-

Prevention

-

Response

٠.

Storage

-

Disposal



Hazardous substances

None known.

Additional labelling

EUH208, Contains Trimethoxyvinylsilane. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

2.3. Other hazards

Additional warnings

No environmental hazard identified as the maximum bioavailable concentration of Octamethylcyclotetrasiloxane (D4) is lower than the classification cut-off value (see Section 12 of this SDS).

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Identifiers	% w/w	Classification	Note
CAS No.: 2768-02-7 EC No.: 220-449-8 REACH: 01- 2119513215-52-XXXX Index No.: 014-049-00-0	<1%	Flam. Liq. 3, H226 Skin Sens. 1B, H317 Acute Tox. 4, H332	
CAS No.: 556-67-2 EC No.: 209-136-7 REACH: 01-2119529238-36 Index No.: 014-018-00-1	<0.1%	Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)	
CAS No.: 104-76-7 EC No.: 203-234-3 REACH: Index No.:	<0.05%	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	[1]
CAS No.: 7664-38-2 EC No.: 231-633-2 REACH: 01-2119485924-24-XXXX Index No.: 015-011-00-6	<0.05%	Skin Corr. 1B, H314 (SCL: 25.00 %)	[1]
	CAS No.: 2768-02-7 EC No.: 220-449-8 REACH: 01- 2119513215-52-XXXX Index No.: 014-049-00-0 CAS No.: 556-67-2 EC No.: 209-136-7 REACH: 01-2119529238-36 Index No.: 014-018-00-1 CAS No.: 104-76-7 EC No.: 203-234-3 REACH: Index No.: CAS No.: 7664-38-2 EC No.: 231-633-2 REACH: 01-2119485924-24-XXXX	CAS No.: 2768-02-7 EC No.: 220-449-8 REACH: 01- 2119513215-52-XXXX Index No.: 014-049-00-0 CAS No.: 556-67-2 EC No.: 209-136-7 REACH: 01-2119529238-36 Index No.: 014-018-00-1 CAS No.: 104-76-7 EC No.: 203-234-3 REACH: Index No.: CAS No.: 7664-38-2 EC No.: 231-633-2 REACH: 01-2119485924-24-XXXX	CAS No.: 2768-02-7 EC No.: 220-449-8 REACH: 01- 2119513215-52-XXXX Index No.: 014-049-00-0 CAS No.: 556-67-2 EC No.: 209-136-7 REACH: 01-2119529238-36 Index No.: 014-76-7 EC No.: 203-234-3 REACH: Index No.: CAS No.: 7664-38-2 REACH: 01-2119485924-24-XXXX Flam. Liq. 3, H226 Skin Sens. 1B, H317 Acute Tox. 4, H332 Skin Sens. 1B, H317 Acute Tox. 4, H332 Skin Irrit. 2, H361f Aquatic Chronic 1, H410 (M=10) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Skin Corr. 1B, H314 (SCL: 25.00 %)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.



If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Room temperature 18 to 23°C



Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-ethylhexan-1-ol

Long term exposure limit (8 hours) (mg/m³): 5,4

Long term exposure limit (8 hours) (ppm): 1

Short term exposure limit (15 minutes) (mg/m³): 10,8

Short term exposure limit (15 minutes) (ppm): 2

Annotations:

E = Substance has an EC limit.

phosphoric acid ... %

Long term exposure limit (8 hours) (mg/m³): 1

Short term exposure limit (15 minutes) (mg/m³): 2

Annotations:

E = Substance has an EC limit.

Ethanol (released in small quantities during vulcanisation)

Long term exposure limit (8 hours) (mg/m³): 1900

Long term exposure limit (8 hours) (ppm): 1000

Statutory order 202 on exposure limits for substances and mixtures (21/02/2023)

DNEL

Trimethoxyvinylsilane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	630 μg/kgbw/day
Long term – Systemic effects - Workers	Dermal	910 μg/kgbw/day
Long term – Systemic effects - General population	Inhalation	6.8 mg/m³
Long term – Systemic effects - Workers	Inhalation	27.6 mg/m³
Short term – Systemic effects - General population	Inhalation	54.4 mg/m³
Short term – Systemic effects - Workers	Inhalation	73.6 mg/m³
Long term – Systemic effects - General population	Oral	630 μg/kgbw/day

PNEC

Trimethoxyvinylsilane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		400 μg/L
Freshwater sediment		1.5 mg/kg
Intermittent release (freshwater)		1.21 mg/L
Marine water		40 μg/L
Marine water sediment		150 μg/kg
Soil		60 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See



occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

In the event the work process is within scope of the Danish statutory order on work with code numbered products (Work Inspectorate Order no. 302/1993), then personal protection equipment shall be selected as set out herein. If applicable, please refer to the code number of this product in section 15.

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Туре	Class	Colour	Standards	
If used in small and very badly ventilated rooms (not relevant if the room is well ventilated)	AX		Brown	EN14387	(B)

Skin protection

No specific requirements.

Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
	Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	

When applying the sealant with a caulking gun and when finishing with a joint nail, work can be carried out without gloves if skin contact is avoided.

Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Paste

Colour

Transparent

Odour / Odour threshold

Characteristic

рΗ

Testing not relevant or not possible due to the nature of the product.

Density (q/cm³)

1,0-1,10

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Testing not relevant or not possible due to the nature of the product.

Phase changes



Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Trimethoxyvinylsilane

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 7100 mg/kg ·

Product/substance Trimethoxyvinylsilane

Species: Rabbit Route of exposure: Dermal



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Test: LD50 Result: 3200 mg/kg·

Product/substance Trimethoxyvinylsilane

Species: Rat
Route of exposure: Inhalation
Test: LD50
Result: 16,8 mg/l/4h ·

Product/substance phosphoric acid ... %

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 1530 mg/kg

Skin corrosion/irritation

Product/substance Trimethoxyvinylsilane

Species: Rabbit Duration: 96 hours

Result: No adverse effect observed (Not irritating)

Serious eye damage/irritation

Product/substance Trimethoxyvinylsilane

Species: Rabbit

Duration: No data available.

Result: Adverse effect observed (Irritating)

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance Trimethoxyvinylsilane

Test method: OECD 406 Species: Guinea pig

Result: No adverse effect observed (not sensitising)

Other information: Test system: Maximizing test

Product/substance Trimethoxyvinylsilane

Test method: OECD 406 Species: Guinea pig

Result: No adverse effect observed (not sensitising)

Other information: Test system: Buehler Test

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

Not applicable.

Other information

Ethanol (released in small quantities during vulcanisation) has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information



12.1. Toxicity

The maximum concentration of Octamethylcyclotetrasiloxane (D4) in the aquatic environment is estimated to be below the established no-effect threshold (<0.0079 mg/l) for aquatic organisms (based on partition coefficient, tested on similar products).

12.2. Persistence and degradability

Product/substance Trimethoxyvinylsilane

Biodegradable: No

Test method: Result:

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 14.5 Other PG* Env** information:
ADR		-	
IMDG		-	
IATA		-	

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

^{**} Environmental hazards



Code number (1993): 00-1.

Sources

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on

classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

Nο

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H361f, Suspected of damaging fertility.

H410, Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.



The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en