

Product Information:

Adhesive Lacquer 319

For hobby applications as both adhesive and lacquer**General description and applications:**

Adhesive Lacquer 319 is a water based all-round adhesive and lacquer. Used for bonding of paper, cardboard, textiles, wood etc.

Used as a lacquer, it gives a glossy transparent surface, suitable for lacquering of tempera colours, collages, cuttings etc.

The product fulfils the requirements of the Danish Association for Art- and Hobby materials and is placed in group A (Danish approval).

**Physical / Chemical properties:****Adhesive:**

Type: Water based dispersion
 Colour: White
 Consistency: Liquid
 Shelf life: Minimum 2 years when kept in tightly closed packaging and stored cool.
 Protect from freezing.

Packaging:

Item no.	Size
20491	250 ml bottle
2049	750 ml bottle

Joint:

Color: Transparent
 Resistance: The glue is soluble in water.

Directions for use:

Preparation: The surfaces must be clean, dry, and free from oil or grease.

Used as adhesive: Apply in a thin layer and press the surfaces together while the adhesive is still wet. For some applications, e.g. wood, it might be necessary to put a light pressure to the material until the adhesive has dried.

Drying time on absorbent surfaces is approx. 10-30 minutes.

Used a lacquer: Apply the Adhesive Lacquer 319 in a thin layer (if necessary, it can be diluted with water)

Application temperature: Room temperature

Cleaning: Wet adhesive can be removed with water. Dry adhesive is removed by soaking in warm water.

Health and safety:

FOR FURTHER INFORMATION ON SAFETY, REFER TO PRODUCT SAFETY DATA SHEET.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
 PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75

