

Product Information:

NBS Building Foam 581

Sealing foam with 0 % isocyanate, flexible and insulating**Product description & use:**

NBS Building Foam 581 is a new type of foam, free of isocyanates, and based upon the latest technology, which provides unique properties:

- ▶ 0 % isocyanate – does not require epoxy certificate
- ▶ Permanently more elastic than traditional foam for sealing
- ▶ Can be over painted

NBS Building Foam 581 demonstrates high insulation property, and bonds to most building materials.

Is used for sealing and insulation around window- and doorframes, pipe outlets, in cavities, between elements of walls and more.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.

**Physical / chemical data:****Uncured foam:**

Type:

1-component isocyanate free STP-foam

Shelf life:

12 months in unopened packaging, if stored cool.

See production date on the can. The cans must always be stored in upright position.

Packaging:

Item nr.	Colour	Size
7638	White	500 ml can
76381	White	750 ml can

Cured foam:

Colour:

White

Paintable:

Yes

Thermal conductivity:

$\lambda = 0,033 \text{ W/m}^\circ\text{C}$ (DIN 52612)

Density:

27 – 30 kg/m³

Temperature:

Can resist temperatures from -40 °C to +80 °C,

Short term (max. 1 hour) up till +120 °C.

Sunlight (UV): Should be protected against sunlight



Directions for use:

- Preparation:** *The surfaces must be free of oil, grease, dirt, dust etc. Always make sure that the surfaces are humid before application of the foam, as it only cures in the presence of moisture. NBS Building Foam 581 bonds to most materials, except from polyethylene, silicone and similar smooth surfaces.*
- Application:** *The foam is difficult to remove, therefore wear suitable gloves, working cloths and eye/face protection. Remove the top and mount the can in the NBS foam pistol. Shake the can 15 – 20 times before use.*
- The joint is filled approximately 70%, since the foam will expand significantly immediately after filling. When used in bigger joints it is recommend applying water to the foam surface.*
- If foam is applied at undesirable places, this must be removed immediately with acetone before curing. Please take note that not all materials are resistant to organics solvents.*
- Application temperature:** *Air and surface temperature 5 °C to 30 °C. Ideal temperature is 20°C. Applies to both cans and surroundings.*
- Yield:** *The content of the can yields up to 8-10 litres.*
- Curing:** *NBS Building Foam 581 is tack-free after 50-70 minutes, at 20 °C and 60 % RH.*
- Treatment:** *The foam must be protected against sunlight. After curing NBS Building Foam 581 can be painted with most paints and lacquers.*
- Cleaning:** *Uncured foam can be removed with acetone. Cured foam can only be removed mechanically or with PU Remover 912.*

Health and safety:

For further information on safety, please refer to product safety datasheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**