

Product Information:

LD Filler Coarse 624

Ready-mixed coarse-grained low-density filler

General description and typical applications:

LD Filler Coarse 624 is a ready-mixed coarse-grained filler with high filling ratio and low density. It is extremely easy to apply and sand.

The filler is suitable for indoor filling of walls and ceilings of plaster, concrete, plaster board etc. in dry rooms.

LD Filler Coarse 624 has a high filling ratio and minimum shrinkage. It can be painted with dispersion- and alkyd-based paints.

LD Filler Coarse 624 meets the strict environmental and indoor air quality requirements required for the Nordic Eco label, Emission and M1 certifications.



Physical / chemical data:

Filler:

Type: Low density filler based on vinyl acetate copolymer dispersion
 Colour: Light grey
 Consistency: Paste
 Density: approx. 1.0 kg/liter
 Shelf life: Minimum 12 months in unopened packing if stored cool.
 Protect from freezing.

Packaging:

Item no.	Size
7972	5 ltr
7973	10 ltr

Cured filler:

Paintable: Yes
 Resistance: The filler is not water resistant.



Directions for use:

- Preparation:** *All surfaces must be clean and free from dust and loose particles. Slightly smudging or strongly absorbent foundations must be primed with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Application:** *LD Filler Coarse 624 is applied with a putty knife in layers up to 10 mm*
- When filling layers of more than 4 mm the filler must be applied over a number of times, and be almost completely dry between each filling, to reduce the risk of shrinkage or formation of cracks.*
- If the next layer is applied too soon, the risk of shrinkage and crack formation is increased.*
- Spreading rate:** *1 m²/liter (1 mm layer thickness)*
- Drying time:** *The drying time of the filler is depending on the thickness of the layer, type of surface, temperature, humidity, ventilation etc. Under normal circumstances it is expected that the filler is dry after 8-10 hours.*
- Cleaning:** *Clean tools and skin with water. Cured filler can be dissolved mechanically or by soaking in water.*

For additional safety information, refer to the product safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**