

Product Information:

Light Weight Filler 628

Fast curing, easy to apply, no shrinkage**General description and application:**

Light Weight Filler 628 is a fast curing white pre-mixed light weight filler, suitable for filling of smaller holes and cracks in bricks, plaster, concrete, wood etc.

Light Weight Filler 628 is easy to apply due to its special consistency, it is easy to sand, do not crack or shrink, takes nails and screws and has good resistance to water.

It should be protected against moisture / rain during curing.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.

**Physical / chemical data:****Filler:**

Type: Acrylic based filler
 Colour: White
 Consistency: Paste, thixotropic
 Density: approx. 0.6 kg/liter
 Shelf life: Minimum 24 months in unopened packing if stored cool.
 Protect from freezing.

Packaging:

Item no.	Size
7766	150 ml tube
7767	950 ml can

Cured filler:

Paintable: Yes
 Resistance: Water: Good but must be protected against direct water.



Directions for use:

- Preparation:* All surfaces must be clean and free from dust and loose particles. Moisten the surface slightly.
- Application:* Light Weight Filler 628 is applied with a filling knife. If the knife is moistened, it will leave a smooth finish.
- If the filler is to dry, it can be mixed slightly with water.*
- Drying time:* Approx. 1 hour – depending on thickness and temperature.
- Sanding:* If necessary, sand the filler after complete drying. The filler is paintable with most paint types, however, the filler must be primed before painted with alkyd-based paint.
- Cleaning:* Clean tools and skin with water. Cured filler can only be dissolved mechanically.

Health and safety:

For further information on safety, please refer to product safety datasheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**