

SAFETY DATA SHEET

Building Foam 580

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Building Foam 580

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Sealing foam

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Dana Lim A/S

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

Fax: +45 56 64 00 90

Contact person

Product Safety Department

E-mail

info@danalim.dk

SDS date

2021-08-20

SDS Version

3.0

Date of previous version

2021-08-19 (2.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

▼ 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2. Label elements

▼ Hazard pictogram(s)



Signal word

Danger

▼ Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Safety statement(s)

▼ General

Keep out of reach of children. (P102)

▼ Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not spray on an open flame or other ignition source. (P211)

Do not pierce or burn, even after use. (P251)

▼ Response

-

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

▼ Disposal

-

▼ Hazardous substances

No special

2.3. Other hazards

▼ Additional labelling

EUH208, Contains Trimethoxyvinylsilane. May produce an allergic reaction.

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

▼ 3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 REACH: 01-2119485395-27 Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	
Dimethyl ether	CAS No.: 115-10-6 EC No.: 204-065-8 REACH: 01-2119472128-37-xxxx Index No.: 603-019-00-8	3-5%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	[1]
tris (2-chlor-1-methylethyl) phosphat	CAS No.: EC No.: 911-815-4 REACH: 01-2119486772-26 Index No.:	3-5%	Acute Tox. 4, H302 (ATE: 632.00 mg/kg)	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 REACH:	3-5%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	

	Index No.: 601-003-00-5		
Trimethoxyvinylsilane	CAS No.: 2768-02-7	<1%	Flam. Liq. 3, H226
	EC No.: 220-449-8		Skin Sens. 1B, H317
	REACH:		Acute Tox. 4, H332
	Index No.: 014-049-00-0		

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

▼ 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction to predisposed persons.

▼ 4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Given that it does not present and hazard gas supplies shall be disrupted immediately. Removal of pressurized containers or attempting to cool with water shall be entrusted the fire brigade.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

▼ 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
Dimethyl ether

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 766

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 958

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

Product/substance	Dimethyl ether
DNEL	1894 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

Product/substance	Dimethyl ether
DNEL	471 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population

PNEC

Product/substance	Dimethyl ether
PNEC	160 mg/l
Route of exposure	Sewage treatment plant
Duration of Exposure	

Product/substance	Dimethyl ether
PNEC	0,045 mg/kg
Route of exposure	Soil
Duration of Exposure	

Product/substance	Dimethyl ether
PNEC	1,549 mg/l
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	Dimethyl ether
PNEC	0,155 mg/l
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	Dimethyl ether
PNEC	0,016 mg/l
Route of exposure	Marine water
Duration of Exposure	

Product/substance	Dimethyl ether
PNEC	0,681 mg/kg
Route of exposure	Freshwater sediment
Duration of Exposure	

Product/substance	Dimethyl ether
PNEC	0,069 mg/kg
Route of exposure	Marine water sediment
Duration of Exposure	

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Adequate ventilation must be ensured for all gases. Where natural ventilation is not possible (cellar rooms), artificial ventilation must be installed. It is advantageous to store it in a lattice shed outdoors, as ventilation is no longer necessary in this case.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally


Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
AX	-	Brown	EN14387	
If used in small and very badly ventilated rooms (not relevant if the room is well ventilated)	AX	-	Brown	EN14387


Skin protection

Recommended	Type/Category	Standards
Antistatic and fireproof protective clothing. Limited protection against flames.		EN 1149-1: 2006, EN 1149-2: 1997, EN 1149-3: 2004; EN 168:2002, EN ISO 14116:2015, EN 1149-5:2018




Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to	EN 166:2002 EN ISO 4007:2018



Type	Standards
the manufacturer´s instructions. Use if there is a risk of splashing.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

White

Odour / Odour threshold

Characteristic

pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

1.02

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Testing not relevant or not possible due to nature of the product.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

Boiling point (°C)

-12.00 °C

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Relative vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

-83.00 °C

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

460 °C

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	7100 mg/kg ·
Other information	

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	3200 mg/kg ·
Other information	

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LD50
Result	16,8 mg/l/4h ·
Other information	

Skin corrosion/irritation

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Rabbit
Duration	96 hours
Result	No adverse effect observed (Not irritating)
Other information	

Serious eye damage/irritation

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Rabbit
Duration	No data available.
Result	Adverse effect observed (Irritating)
Other information	

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Guinea pig
Result	No adverse effect observed (not sensitising)
Other information	

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Long term effects

No special

Endocrine disrupting properties

No special

Other information

No special

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	191 mg/l ·
Other information	

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Daphnia
Compartment	

Duration	48 hours
Test	EC50
Result	169 mg/l ·
Other information	

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Daphnia
Compartment	
Duration	21 days
Test	NOEC
Result	25 mg/l ·
Other information	

Product/substance	Trimethoxyvinylsilane
Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	NOEC
Result	25 mg/l ·
Other information	

12.2. Persistence and degradability

Product/substance	Trimethoxyvinylsilane
Biodegradable	No
Test method	
Result	

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

No special

SECTION 13: Disposal considerations

▼ 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

UN- or ID number	UN proper shipping name	Labels	Packing group	Tunnel restriction code
1950	AEROSOLS, flammable	2.1		2 (D)

IMDG

UN- or ID number	UN proper shipping name	Labels	Packing group	EmS
1950	AEROSOLS, flammable	2.1		F-D, S-U

MARINE POLLUTANT

No

IATA

UN- or ID number	UN proper shipping name	Labels	Packing group
1950	AEROSOLS, flammable	2.1	

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Additional information

Not applicable

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29)

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information**Full text of H-phrases as mentioned in section 3**

H220, Extremely flammable gas.
H226, Flammable liquid and vapour.
H280, Contains gas under pressure; may explode if heated.
H302, Harmful if swallowed.
H317, May cause an allergic skin reaction.
H332, Harmful if inhaled.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

The safety data sheet is validated by

ESQ

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a

blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en