

#### SAFETY DATA SHEET

# Low Density Filler Medium Extra 623

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

Low Density Filler Medium Extra 623

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Fille

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

## Company and address

#### Dana Lim A/S

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

#### Contact person

**Product Safety Department** 

E-mail

info@danalim.dk

Revision

14/12/2022

**SDS Version** 

1.0

## 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

## 2.2. Label elements

Hazard pictogram(s)

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Safety statement(s)

General

-

Prevention

\_\_\_

Response

Storage

-

Disposal

-

Hazardous substances



None known.

#### Additional labelling

EUH208, Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210, Safety data sheet available on request.

## 2.3. Other hazards

## Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
1,2-benzisothiazol-3(2H)-one	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 911-418-6 UK-REACH: Index No.:	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	
vinyl acetate	CAS No.: 108-05-4 EC No.: 203-545-4 UK-REACH: Index No.: 607-023-00-0	<0.0015%	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT SE 3, H335 Carc. 2, H351	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

## Other information

[1] European occupational exposure limit.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact



Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

## Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### **Burns**

Not applicable.

## 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

None known.

#### Information to medics

Bring this safety data sheet or the label from this product.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Some metal oxides

## 5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

## 6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

## 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

> 0°C

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

## 7.3. Specific end use(s)



This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

vinyl acetate

Long term exposure limit (8 hours) (ppm): 5

Long term exposure limit (8 hours) (mg/m³): 17,6

Short term exposure limit (15 minutes) (ppm): 10

Short term exposure limit (15 minutes) (mg/m³): 35,2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

## **DNEL**

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration	Route of exposure	DNEL
Long term – Local effects - General population	Inhalation	20 μg/m³
Long term – Local effects - Workers	Inhalation	20 μg/m³
Short term – Local effects - General population	Inhalation	40 μg/m³
Short term – Local effects - Workers	Inhalation	40 μg/m³
Long term – Systemic effects - General population	Oral	90 μg/kgbw/day
Short term – Systemic effects - General population	Oral	110 μg/kgbw/day

## vinyl acetate

•		
Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	420 μg/kgbw/day
Long term – Local effects - Workers	Inhalation	17.6 mg/m³
Long term – Systemic effects - Workers	Inhalation	17.6 mg/m³
Short term – Local effects - Workers	Inhalation	35.2 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	35.2 mg/m <sup>3</sup>

## **PNEC**

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Freshwater Freshwater sediment 27 µg/kg Intermittent release (freshwater) 3.39 µg/L Intermittent release (marine water) 3.39 µg/L Marine water 3.39 µg/L 27 µg/kg	Route of exposure	<b>Duration of Exposure</b>	PNEC
Intermittent release (freshwater)  Intermittent release (marine water)  Marine water  3.39 µg/L  3.39 µg/L	Freshwater		3.39 μg/L
Intermittent release (marine water)  Marine water  3.39 µg/L  3.39 µg/L	Freshwater sediment		27 μg/kg
Marine water 3.39 µg/L	Intermittent release (freshwater)		3.39 μg/L
	Intermittent release (marine water)		3.39 μg/L
Marine water sediment 27 μg/kg	Marine water		3.39 μg/L
	Marine water sediment		27 μg/kg
Sewage treatment plant 230 µg/L	Sewage treatment plant		230 μg/L
Soil 10 μg/kg	Soil		10 μg/kg

## vinyl acetate

Route of exposure	Duration of Exposure	PNEC
Freshwater		16 μg/L
Freshwater sediment		67 μg/kg
Intermittent release (freshwater)		126 μg/L
Marine water		1.6 μg/L
Marine water sediment		6.7 μg/kg
Sewage treatment plant		6 mg/L
Soil		3.5 μg/kg



#### 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

## General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

#### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

## Measures to avoid environmental exposure

No specific requirements.

## 8.3. Individual protection measures, such as personal protective equipment

#### Generally

Use only UKCA marked protective equipment.

#### Respiratory Equipment

Avoid breathing abrasive dust. When sanding, the dust can be removed at the source with a minimum class M vacuum cleaner connected to the sanding mashine.

Work situation	Туре	Class	Colour	Standards	
Upon during sanding of treated areas (No special precautions when handling the wet product)		P3	White	EN149	

## Skin protection

No specific requirements.

## Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.1	> 480	EN374-2, EN388	



## Eye protection

No specific requirements.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

#### Physical state

**Paste** 

Colour

Gray

#### Odour / Odour threshold

Testing not relevant or not possible due to the nature of the product.

рΗ

8-9

Density (g/cm³)

0.98

## Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

## Particle characteristics

Testing not relevant or not possible due to the nature of the product.

## Phase changes



## Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

## Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

## Vapour pressure

Testing not relevant or not possible due to the nature of the product.

#### Relative vapour density

Testing not relevant or not possible due to the nature of the product.

#### Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

## Data on fire and explosion hazards

## Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

## Auto-Ignition (°C)

Testing not relevant or not possible due to the nature of the product.

#### Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

#### Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

## Solubility

## Solubility in water

Completely soluble

#### n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

#### Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

#### 9.2. Other information

## Other physical and chemical parameters

No data available.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No data available.

## 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

## 10.3. Possibility of hazardous reactions

None known.

## 10.4. Conditions to avoid

None known.

## 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

## 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

Product/substance

1,2-benzisothiazol-3(2H)-one

Test method

Species Rat
Route of exposure Dermal
Test LD50
Result >2000 mg/L

Other information

Product/substance

1,2-benzisothiazol-3(2H)-one

Test method Species

Rat



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Route of exposure Oral
Test LD lo
Result 597 mg/L

Other information

Product/substance Test method Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Species Rat Route of exposure Oral Test LD50

Result 49,6-75 mg/kg ·

Other information

Product/substance Test method Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Species Rat
Route of exposure Inhalation
Test LC50

Result 0,33 mg/l, 4 h aerosol ·

Other information

Product/substance

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method
Species Rabbit
Route of exposure Derma
Test LD50

Route of exposure Dermal
Test LD50
Result 141 mg/kg

Other information

Skin corrosion/irritation

Product/substance 1,2-benzisothiazol-3(2H)-one

Test method

Species Rabbit

Duration No data available.

Result Adverse effect observed (Moderately irritating)

Other information

#### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

## Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance

1,2-benzisothiazol-3(2H)-one

Test method Species

Result Adverse effect observed (sensitising)

Other information

Product/substance Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method OECD 406 Species Guinea pig

Result Adverse effect observed (sensitising)

Other information

## Germ cell mutagenicity

Based on available data, the classification criteria are not met.

## Carcinogenicity

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

#### 11.2. Information on other hazards

## Long term effects

None known.

#### **Endocrine disrupting properties**

None known.

#### Other information

vinyl acetate has been classified by IARC as a group 2B carcinogen.

## SECTION 12: Ecological information

12.1. Toxicity

Test Result

Product/substance

1,2-benzisothiazol-3(2H)-one

Test method

Species Fish

Compartment

Duration

96 hours LC50 0,74 mg/L

Other information

Product/substance

1,2-benzisothiazol-3(2H)-one

Test method

Species

Daphnia

Compartment

Duration 48 hours
Test EC50
Result 2,44 mg/L

Other information

Product/substance

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species

Algae

Compartment

Duration 72 hours
Test EC50
Result 0,027 mg/l

Other information

## 12.2. Persistence and degradability

Product/substance Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Biodegradable Yes

Test method OECD 301 D Result >60%

## 12.3. Bioaccumulative potential

Product/substance Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Potential bioaccumulation No

LogPow No data available.

BCF 3.6

Other information

## 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

## 12.6. Endocrine disrupting properties

None known.

## 12.7. Other adverse effects

None known.

## **SECTION 13: Disposal considerations**

## Waste treatment methods



Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### EWC code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09

## Specific labelling

Not applicable.

## Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## **SECTION 14: Transport information**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

<sup>\*</sup> Packing group

#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

#### 14.6. Special precautions for user

Not applicable.

## 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Restrictions for application

None known.

## Demands for specific education

No specific requirements.

## SEVESO - Categories / dangerous substances

Not applicable.

## Additional information

Not applicable.

## Sources

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

## 15.2. Chemical safety assessment

No

## **SECTION 16: Other information**

## Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H225, Highly flammable liquid and vapour.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

<sup>\*\*</sup> Environmental hazards



H330. Fatal if inhaled.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H351, Suspected of causing cancer.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

## Additional information

Not applicable.

## The safety data sheet is validated by

**Product Safety Department** 

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en