

Product Information:

Tooling Liquid Concentrate 902

Reduces risk of adhesion failure, for all sealants.


General description and application:

Tooling Liquid Concentrate 902 is especially developed for tooling of sealants based on silicone, MS-polymer and polyurethane.

Using Tooling Liquid 902 reduces the risk of adhesion failure and reduces the tendency of sealant sticking to the tooling stick. Suitable for both wet and dry tools.

Notice: The product is in concentrated form and must be diluted 1:10 with water.



Member of  Danish Association of Sealant Applicators & Manufactures.

Physical / chemical properties:

- Colour: *Translucent*
- Consistency: *Thin liquid*
- Specific gravity: *App. 1,0 kg/ltr*
- pH-value: *6-8*
- Shelf life: *Minimum 2 years in unopened packing, if stored cool and dry.*
- Packaging:

Item no.	Size
4993	5 ltr can



Directions for use:

Application temperature: Can be applied at temperatures from +5 °C to +40 °C.

Application: **The Tooling Liquid 902 is used diluted 1:10 with water.** Store joint stick immersed in the tooling liquid before handling of the sealant, alternatively spray the liquid directly on the sealant and tool it with a dry or wet joint stick.

Tooling Liquid 902 is also suitable if the joint is finished with a spatula.

Note that it is possible to refill joints that have been handled with Tooling Liquid 902.

Note: When using tooling liquid on a spray bottle, be aware that the tooling liquid is applied **directly** to the sealant, - tooling liquid applied or spilled on adjacent surfaces can cause:

- risk of corrosion when applied to steel
- risk of color change when applied to porous and sensitive surfaces such as natural stone and composite
- risk of optical pollution/degradation of surface when used on glass, lacquered/treated metal and plastic

Avoid use in direct full sunlight

To determine suitability of adjacent surfaces, as well the choice of application method and any covering material, tests should be performed.

Any excess tooling liquid must be removed immediately from adjacent surfaces

Cleaning: Surfaces can be cleaned with plenty of clean water or with Wipes Sensitive 915.

Health and safety:

For further information on safety, refer to product safety datasheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**