


Product Information:

Primer 963

Primer for porous surfaces**General description & application:**

Primer 963 is special primer that can improve adhesion of MS-, PU- and neutral-curing silicon-based sealants to porous and absorbent mineral surfaces such as plaster, concrete and brick, both indoors and outdoors.

Member of  Danish Association of Sealant Applicators & Manufactures.

**Physical / chemical properties:****Primer:**

Type: 1-component solvent based.
 Colour: Colourless
 Consistency: Liquid
 Shelf life: Minimum 6 months in unopened packing, if stored cool and
 Packaging:

| Item no. | Size |
|----------|---------------------|
| 7577 | 250 ml metal bottle |

Directions for use:

Preparation: All surfaces must be clean, dry, free of grease, dust, and loose particles. The choice of primer must be made after sufficient adhesion- and compatibility tests. If the primer is used indoors – remember to provide sufficient ventilation.

Application: Primer 963 is applied with a soft brush or cloth, in a thin even layer. Application should be made carefully, as the primer will be visible after drying. Use covering tape if necessary. Primer 963 is sensitive to evaporation and there is a risk of a thickening of the product, the bottle should therefore be closed immediately after use.

Yield: For a joint with of 1 cm, a 250 ml bottle will be sufficient to 70-165 m, depending on the absorbency of the substrate.

Drying time: 30 - 60 minutes at 20 °C. The sealant should be applied immediately after complete drying of the primer, to avoid contamination of the primed surface.

Cleaning: The brush can be cleaned with an organic solvent, e.g. acetone.

Health and safety: For further information on safety, refer to product safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
 PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**