

Product Information:

LD Filler Coarse 624

Ready-mixed coarse-grained low-density filler

General description and application:

LD Filler Coarse 624 is a ready-mixed coarse-grained filler with high filling ratio and low density. It is extremely easy to apply and sand.

The filler is suitable indoor in dry rooms for plastering of walls and ceilings of, concrete, lightweight concrete, plaster, plasterboard etc.

LD Filler Coarse 624 can be painted with most types of paint.

LD Filler Coarse 624 meets the strict environmental and indoor air quality requirements required for the Nordic Eco label and Emission certifications.



Physical / chemical data:

Filler:

Type: Low density filler based on vinyl acetate copolymer dispersion
 Colour: Light grey
 Consistency: Paste
 Density: Approx. 1.0 kg/l.
 Shelf life: Minimum 12 months in unopened packing if stored cool.
 Protect from freezing.

Packaging:

Item no.	Size
7972	5 l.
7973	10 l.

Cured filler:

Paintable: Yes
 Resistance: The filler is not water resistant.



Directions for use:

- Preparation:** *All surfaces must be clean and free from dust and loose particles.
Poorly bonded or highly absorbent substrates must be primed with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Application:** *LD Filler Coarse 624 can be applied with a putty knife in layer thickness of up to 10 mm. To minimize the risk of shrinkage and cracking, the putty should be applied in several layers at a layer thickness of more than 4 mm, and it should be almost completely dry between each application.*
- Premature application of the next layer increases the risk of shrinkage and cracking.*
- Spreading rate:** *Wide spreading: 1 m²/l. (1 mm layer thickness)*
- Drying time:** *The drying time of the filler is depending on the thickness of the layer, type of surface, temperature, humidity, ventilation etc. Under normal circumstances it is expected that the filler is dry after 8-10 hours.*
- Cleaning:** *Clean skin with soap and water.
Tools are cleaned with water while the filler is still wet.
Cured filler can be removed mechanically or by soaking in water.*

Health and safety:

For further information on safety, please refer to product safety datasheet

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**