

# Declaration of Performance

**Nr.: 15651-0521-1-UK**

1. Unique identification of product type:  
**EN 15651-1: F-INT**
2. Identification of construction product:  
**Danaseal Interior 521**  
**Batch number: See product packaging**
3. Intended use of product:  
**Sealant for use in facade elements**  
**Type F-INT**
4. Address and name of the producer:  
**Dana Lim A/S, Københavnsvej 220, 4600 Køge, Danmark**
5. Name and address of authorized representative:  
**Not relevant**
6. System and verification of consistency of the construction product (Annex V):  
**System 4 + 3**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**The notified body Fundacion Tecnalia Research & innovation (1292)**  
**performed the testing of reaction to fire under system 3 and issued a test report**
8. In case of declaration of performance concerning a construction product covered by a European Technical Assessment has been issued:  
**Not relevant**
9. Declared Performance:  
Conditioning: Method A  
Substrate: Aluminium (without primer)

Essential characteristic	Performance	Harmonized technical specification
Reaction to fire	E	EN 15651-1:2012
Release of chemicals dangerous to health and environment	NPD*	
Water and air tightness		
a) Resistance to flow	≤ 5 mm	
b) Loss of volume	≤ 45 %	
c) Tensile properties (secant modulus/elongation at break in %)	≥ 25 %	
d) Durability	Pass	

\*See Material Safety Datasheet



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Køge, 22.10.2014



---

Erik Andersen  
Laboratoriechef