



# TECHNICAL DATASHEET

## DANAFIX

Adhesive for coarse paper

**Product:**  
**DANAFIX 726**

**Date of issue:** 13.05.2013  
(Replaces: 23.10.2012)

**Company** DANA LIM A/S  
Københavnsvej 220, DK-4600 Køge

Ph.: 56 64 00 70, Fax.: 56 64 00 90, [www.danalim.dk](http://www.danalim.dk)  
Technical Service Ph.: 56 64 00 75

**Prepared by:** Laboratory, Kristian K. Pedersen

### Product Description and Application:

DANAFIX 726 is a water based adhesive, for gluing coarse paper. The adhesive sets quickly and gives a high strength.

Packaging size:

Item no.	Size
6695	1000 l container

### Physical / Chemical Properties:

<b>Adhesive:</b>	<b>726</b>
Type:.....	Water based PVAc dispersion
Colour:.....	White
Solid content [%], approx:.....	32
Viscosity [cP], approx:.....	1.200
Density [kg/ltr.], approx:.....	1,1
pH:.....	4 – 5
Shelf life:.....	Min. 12 months in original closed packaging

<b>Cured joint</b>	
Colour:.....	Transparent

## Directions for use:

**Preparation:** All surfaces must clean and dry, free from oil, grease, release agents, dust and loose particles.

**Dilution:** The adhesive is delivered ready for use, but can if necessary be diluted with water.

**Application:** Apply a thin layer of adhesive to one of the surfaces using nozzle, roller or wheel.  
The two parts are gathered together while the adhesive is still wet.

**Application temperature:** 15 – 25 °C

**Cleaning:** Uncured adhesive can be removed with water. Cured adhesive can be removed with hot water.

**Storage:** To be stored cool (max. 20°C) in tightly closed packaging. Should be protected from frost.

**All information's are meant as a guideline. Sufficient test should be carried out to determine final working condition.**

## Safety:

**Hazard Symbols:** None

**Risk and Safety phrases:** None

For further information concerning safety, refer to safety Datasheet.

## Further information:

### **DANA LIM offers a range of adhesives for professionals:**

100-series: Upholstering adhesives

200-series: Flooring adhesives

300-series: Wall adhesives

400-series: Wood adhesives

500-series: Sealants & PU-foams

600-series: Building-additives, fillers etc.

**700-series: Paper-, packaging- and newspaper adhesives**

800-series: Hot melt

900-series: Cleaning-, release agents and hardeners.

### **In the 700-series: Paper-, packaging- and newspaper adhesives offers:**

700-series: Different special adhesives

710-series: Adhesives for paper with a long open time

730-series: Pressure sensitive adhesives

740-series: Gluing of difficult (ex. Waxed) surfaces

750-series: Gluing of lacquered surfaces

760-series: Bookbinder adhesives

770-series: Newspaper adhesives

780-series: Gluing of difficult surfaces (roller or nozzle application)

790-series: Gluing of untreated paper and cardboard

The information and data contained in this data sheet are based on extensive laboratory testing and our practical experiences, and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this technical data sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.