

Product Information:

Sprayable Filler Coarse 634

Ready-mixed coarse grained sprayable low density filler.

General description and applications:

Sprayable Filler Coarse 634 is a ready-mixed coarse grained filler with high filling ratio and low density. It is extremely easy to apply and sand.

The filler is suitable for indoor filling of walls and ceilings of plaster, concrete, plaster board etc. in dry rooms.

Sprayable Filler Coarse 634 has a high filling ratio and minimum shrinkage. It can be painted with dispersion- and alkyd-based paints.

The product meets the indoor air quality requirements required for the Eimicode EC1^{PLUS} certification.

The product is registered in the database for construction products that can be included in the Nordic Ecolabelled construction.

**Physical / chemical data:****Filler:**

Type:	Low density filler based on vinyl acetate copolymer dispersion
Colour:	Light grey
Pigment/Fillers:	Aluminium silicate, expanded perlite and Dolomite
Consistency:	Paste
Density:	approx. 1,0 kg/liter
Shelf life:	Minimum 12 months in unopened packing if stored cool. Protect from freezing.
Packaging:	

Item no.	Size
7995	15 ltr

Cured filler:

Paintable:	Yes
Resistance:	The filler is not water resistant.



Directions for use:

- Preparation:** *All surfaces must be clean and free from dust and loose particles.*
- Non-absorbent and painted foundations are sanded and washed with a cleaning agent. Slightly smudging or strongly absorbent foundations must be primed with Plaster Primer 224 or Plaster Primer Gel Extra 228 after cleaning.*
- Application:** *Sprayable Filler Coarse 634 can be applied with spray equipment that is designed for application of sprayable fillers.*
- When filling a thick layer, the filler must be applied over several times, and be almost completely dry between each filling, to reduce the risk of shrinkage or formation of cracks.*
- If the next layer is applied too soon, the risk of shrinkage and crack formation is increased.*
- Spreading rate:** *1 m²/liter (1 mm layer)*
- Drying time:** *The drying time of the filler is depending on the thickness of the layer, type of surface, temperature, humidity, ventilation etc. Under normal circumstances it is expected that the filler is dry after 8-10 hours.*
- Cleaning:** *Clean tools and skin with water.*
Cured filler can only be dissolved mechanically or by soaking in water.

Health and safety:

For further information on safety, please refer to safety datasheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75