

# Declaration of Performance

Nr.: 15651-0505-1-UK

1. Unique identification of product type:  
**EN 15651-1: F-INT**
2. Identification of construction product:  
**Acryl Extra 505**  
**Batch number: See product packaging**
3. Intended use of product:  
**Sealant for use in interior facade elements**  
**Type F-INT (12.5P)**
4. Address and name of the producer:  
**Dana Lim A/S, Københavnsvej 220, 4600 Køge, Denmark**
5. Name and address of authorized representative:  
**Not relevant**
6. System and verification of consistency of the construction product (Annex V):  
**System 4**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**Not relevant**
8. In case of declaration of performance concerning a construction product covered by a European Technical Assessment has been issued:  
**Not relevant**
9. Declared Performance:  
Conditioning: Method A  
Substrate: Mortar, type M1 (without primer)

Essential characteristic	Performance	Harmonized technical specification
Reaction to fire	NPD	EN 15651-1:2012
Release of chemicals dangerous to health and environment	NPD*	
Resistance to flow	≤ 5 mm	
Loss of volume	≤ 45 %	
Elongation at break	≥ 100 %	


\*See Material Safety Datasheet

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Køge, 03.11.2020



  
Erik Andersen  
Laboratory manager