

GLASS WEB AND FELT

Putting Up and Important Tips!



DANA LIM A/S
Københavnsvej 220
DK-4600 Køge
www.danalim.dk

Technical Service: +45 56 64 00 75
Ph.: +45 56 64 00 70

PUTTING UP GUIDE:



First, clean the wall thoroughly of old wallpaper remains. Then sandpaper and fill the wall (for small holes and cracks use Indoor Filler 611, and for larger holes use Light Filler Fine 621, Medium 622 or Coarse 624, depending on the size of the hole). After drying, have the wall smoothed to remove any irregularities. Pay special attention to the fact that walls are to be quite flush when putting up web and felt.



Remove dust and filler remains. If the wall rubs off easily or is highly absorbent, apply Wall Primer 224, as it increases adhesion and minimizes the consumption of web adhesive.



Cut the glass web in lengths about 10 longer than the height of the wall. The inside of the roll is "wall-side" which is the adhesive side. Apply an even coat of Web Adhesive 212 using a paint roller or brush, and then put up the web immediately after. Use a wallpaper brush to brush the web firm. To eliminate any air pockets, brush from the middle and out. Be aware that the web threads must match.



Once the putting up of the web has been completed, cut off any surplus web from all edges. The web is to be left to dry for a minimum of 12 hours before it may be painted. Using Web Filler 226 a better finish and paint is saved.

Sound Tips:

- Before putting up the first length, mark a vertical line on the wall using a level. Following this line will make a good starting point for getting a straight length, and consequently a fine result.
- In case of obstacles, such as plugs or similar in the middle of a length, cut a diagonal cross corresponding to the corners of the object; when the length has been put up, cut it completely free.
- Glass web will frequently have to be butted edge to edge but may be overlapped at the edges by appr. 3 cm. For a fine, "invisible" joint, cut along the middle of the joint using a hobby knife, and remove the remains.
- Acrylic Sealant may be used where glass web is edging towards f.e. ceiling and skirting board to create a nice look.

Also remember: Filling knife - rule - level - pencil - knife - broom/vacuum cleaner - paint tape - long-brushed paint roller - wallpaper brush.

NOTE: If you are putting up web in a wet room, use a special wet room adhesive. For more information please refer to


www.danalim.dk



Fill wall




Cut web




Apply primer and adhesive



Put up web



Remove surplus web



Apply web filler. The web may now be painted!