



## Maintenance of MS Sealants

Today MS sealants are used more and more on the Danish building sites. This leads to greater and greater interest in how this kind of joints should be maintained.

### MS Polymere

Sealflex Hybrid 522, Danaseal Contractor PF 552 & MS Contractor 550 are based on MS-polymer, which combines the best properties of silicone- and polyurethane sealants. The sealant cures by reaction with moisture to an elastic joint, which has a movement capability of +/- 25%.

Sealflex Hybrid 522, Danaseal Contractor PF 552 & MS Contractor 550 is suitable as a universal construction sealer in buildings, industry and marine, indoor as well as outdoor. It is particularly suitable for expansion joints and sealing tasks, where silicone sealants would have been used earlier, but where the paintability and compatibility of an MS-sealant is required.

Sealflex Hybrid 522, Danaseal Contractor PF 552 & MS Contractor 550 neutral curing, paintable and have excellent resistance to climatic influence.

### Cleaning of Sealants

MS polymere has a tendency to be slight sticky in the surface compared to the more very bright silicones. Hereby you find that the surface gets dirtier than a silicone and needs to be cleaned more often.

When cleaning the window and doors it is a good idea to clean the sealant at the same time, so as it again looks nice and clean in the surface. For this, you can use the same solution, as when you clean your window, a suitable soap solution with a drop of ethanol.

After cleaning it is important to wipe of the sealant with a clean wet lint-free cloth.

Should the sealants be very dirty then it can be an advantage to take a cloth with pure ethanol, and rub directly upon the sealant, but only for a short period of time, and clean afterwards thoroughly with water.

When using cleaners, it is important to be aware of the compatibility with the surrounding materials, in doubtful cases tests should be performed.

The information and data contained is based on extensive laboratory testing and our practical experiences and are meant for helping the user to find best possible working methods. As the working conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information in this "How To Do" information sheet are typical values, intended as a guideline, they should not be regarded as product specifications. Please also refer to our general sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DANMARK –  
INFO@DANALIM.DK**