

Product Information:

Wallpaper Dissolver 220

For removal of old wallpaper.

General description and application:

Wallpaper Dissolver 220 is a water-based product for dissolving wallpaper glue before removal of old wallpapers etc.

Wallpaper Dissolver 220 has very good wetting power, effective absorption and dissolving properties.

**Physical / chemical properties:****Primer:**

Type:

Solution of non-ionic tenside in water

Colour:

Weak yellowish

Consistency:

Liquid

Shelf life:

Minimum 24 months in tightly closed packing if stored dry and cool.

The product should be protected from frost.

Packaging:

Item no.	Size
8701	1 ltr
8702	5 ltr



Directions for use:

- Preparation:** *Non-absorbing or painted wallpaper must be scored before the Wallpaper Dissolver 220 is applied.*
- Mixing ratio:** *The product is mixed with water in the ratio 1-part dissolver to approximately 7 parts of water. The mixing ratio may be varied due to experience with the type of wallpaper and wall.*
- Application:** *The Wallpaper Dissolver 220 is applied to the wallpaper with spray, brush or roller. Application of the dissolver can with good effect be repeated. Wait some minutes between each repetition and stop when the absorption of the wallpaper is at a minimum.*
- After approx. 10 – 15 minutes the wallpaper can be removed with a putty knife.*
- If necessary, the treatment is repeated.*
- Yield:** *5 - 10 m²/liter, depending on how absorbing the surface is.*
- Cleaning:** *Wash hands and skin with soap and water.
Remove stains and spots immediately with a damp cloth.
Clean tools with lukewarm water.*

Health and safety:

For further information on safety, please refer to product safety data sheet.

The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**