

**Product Information:**

# Plaster Primer 224

**Water-based primer – for indoor and outdoor use****General description and typical application:**

Plaster Primer 224 is a water-based primer, suitable for all porous mineral surfaces both indoor and outdoor.

Plaster Primer 224 has good penetration into porous substrates, and thus prepare it for the next surface treatment.

It is used to improve the adhesion on concrete, plasterboard and filled areas, before mounting of wallpaper, fibre glass web etc.

The product is diffusion open.

**Physical / chemical properties:****Primer:**

Type:	Water-based styrene-acrylic dispersion
Colour:	Blue green
Consistency:	Liquid
Dry solid content:	14 %
Shelf life:	Minimum 24 months in tightly closed packing if stored dry and cool. The product should be protected from frost.

**Packaging:**

Item no.	Size
7430	1 ltr
7431	2.5 ltr
7432	5 ltr
7433	10 ltr



**Directions for use:**

- Preparation:* The surface must be clean, dry and free from wallpaper residues. Filled areas must be thoroughly cleaned after sanding.
- Dilution:* If necessary, the primer can be diluted with water. If Plaster Primer 224 is used for pre-treatment before mounting wallpaper or fibre glass web, it should be diluted 1:1 with water.
- Application:* Apply the primer with brush, roller or spray. If the surface is very absorbing, the primer may have to be applied in two layers.
- Application temperature:* Can be applied from +5°C. There must not be any condensation water on the surface when used outdoors.
- Spreading rate:* 5 - 10 m<sup>2</sup>/lit, depending on how absorbing the surface is.
- Drying time:* 1 - 2 hours, depending on how absorbing the surface is.
- Cleaning:* Wash hands and skin with soap and water.  
Remove stains and spots immediately with a damp cloth.  
Clean tools with lukewarm water.  
Dried primer can be removed mechanically or dissolved by soaking in water.

**Health and safety:**

For further information on safety, refer to product safety data sheet.

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK**

**PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**