

**Product Information:**

# Plaster Primer 224

**Water based primer – for indoor and outdoor use**

**General description and typical applications:**

Plaster Primer 224 is water-based primer, suitable on all porous mineral surfaces both indoor and outdoor.

Plaster Primer 224 have good penetration into porous substrates, due to a very small particle size.

It is used to improve the bonding on concrete, plasterboard and where fillers have been used, before mounting of wallpaper, fibre glass web etc.



**Physical / chemical properties:**

**Primer:**

- Type: Water based styrene-acrylic dispersion
- Colour: Blue green
- Consistency: Liquid
- Dry solid content: 14 %
- Shelf life: Minimum 24 months in tightly closed packing if stored dry and cool. The product should be protected from frost.

**Packaging:**

Item no.	Size
7430	1 ltr
7431	2.5 ltr
7432	5 ltr
7433	10 ltr



**Directions for use:**

- Preparation:* The foundation must be clean, dry and free from wall-paper remnants. Filled areas must be very carefully cleaned after sanding.
- Dilution:* If necessary, the primer can be diluted with water. If Plaster Primer 224 is used for pre-treatment before mounting wallpaper or fibre glass web, it should be diluted 1:1 with water.
- Application:* The primer is applied with a brush, roller or spray. If the surface is very absorbing, the primer should be applied in 2 layers.
- Yield:* 5 - 10 m<sup>2</sup>/liter, depending on how absorbing the surface is.
- Drying time:* 1 - 2 hours, depending on how absorbing the surface is.
- Cleaning:* Uncured primer is removed with water and soap. Tools are cleaned with water while the primer is still wet.

*For further information concerning safety, refer to Safety Datasheet.*

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK**

**PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**