

**Product Information:**

# Indoor Filler 611



**Gypsum based powder filler**

**General description and applications:**

*Indoor Filler 611 is gypsum-based powder filler for indoor use. It is used for filling of small cracks and holes on walls and ceilings of plaster, concrete, wood etc. in dry rooms.*

*Indoor Filler 611 is very easy to mix and gives a white filling. It can be used in a very thick layer without any risk of shrinking and cracking.*

*Indoor Filler 611 can be used for modeling since it after curing can be sawed, scraped and sanded. In addition, it can be added tinted pigments up to 5%.*

**Physical / chemical data:**

**Filler:**

Type: Gypsum-based powder  
 Colour: White  
 Shelf life: Minimum 6 months in tightly closed packing if stored dry.

**Packaging:**

Item no.	Size
7760	500 g
7761	2 kg
7762	5 kg



## Directions for use:

- Preparation:** *The surface must be adsorbent and clean. Old wallpaper, loose particles and dust must be removed. Non-absorbent surfaces must be sanded, a highly absorbent surface must be wetted with water and wood must be primed before filling.*
- Working conditions:** *Temperature must be over 5°C.*
- Mixing:** *The powder is mixed in ratio 1part water to 2 parts powder. It's easier to mix by adding the powder in water, then leave the mass for 2 minutes and then stir until lump-free  
If the filler is used for filling big holes, decrease the amount of water.*
- Application:** *Indoor Filler 611 is applied with a filling knife slightly above level, so after a light sanding come to the level with the surrounding surfaces. Please note that with highly absorbent, ungrounded surface, do not apply under 1 mm layer thickness, as the water will thereby be pulled out of the mass and the hardening will be left out.*
- Yield:** *Approx. 950 g powder per m<sup>2</sup>/mm.*
- Drying time:** *1 - 2 hour depends on layer thickness.*
- Cleaning:** *Tools clean with water immediately after use*

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK  
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**