

**Product Information:**

# Quick Filler 614

**Cement based powder filler**

**General description and typical applications:**

*Quick Filler 614 is a fast curing cement-based powder filler for repairing large and small damages, cracks and uneven surfaces indoor and outdoor.*

*Quick Filler 614 is used for levelling most substrates, such as. plaster, concrete, lightweight concrete, plasterboard, wood panels, etc. Can be levelled even in very thick layers without risk of shrinkage or shrinkage cracks.*

*Quick Filler 614 is particularly suitable for mounting and repairs related to electrical and plumbing work for example by solid casting of electric sockets, cables, brackets for radiators, downspouts, railings and the like. It is also suitable as water-resistant filler in 'wet room' and can carry tile coatings and similar heavy-duty coatings.*



**Physical / chemical data:**

- Filler:**
- Type: Cement-based powder
- Colour: Grey
- Shelf life: Min. 6 months if stored dry in unopened packing.
- Packaging:

Item no.	Size
7756	1 kg



## **Directions for use:**

- Preparation:** *The surface must be clean and free from loose particles. Dry surfaces are moistened with water to improve the adhesion. The temperature of the surface should be minimum 5 °C.*
- An improved adhesion to the substrate can be achieved by using Primer 600.*
- Mixing:** *1 kg powder is mixed with 200 gr. water. Then the consistency will be fluid.  
1 kg powder is mixed with 160 gr. water. Then the consistency will be more solid.*
- Always use clean, cold water. If the product is used at low temperatures, it may be advantageous to use lukewarm (about 20 °C) water as it will accelerate the curing process, and application time will be reduced*
- The filler is mixed thoroughly for 3 – 4 minutes, preferably by using an electric mixer, until the filler is free of lumps.*
- Pot-life:** *Approx. 5-10 min. at 20 °C.*
- Application:** *Quick Filler 614 is applied and filled with a filling knife.  
The maximum layer thickness is 5 cm, which must be applied in two layers*
- Drying time:** *Approx. 15 min. at 20 °C.*
- Treatment:** *The filler is paintable after 1 – 2 days, dependent on temperature and thickness of the layer.*
- Cleaning:** *Tools are cleaned with water before the filler cures.*

*For further information, please refer to safety data sheet.*

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE – DENMARK – INFO@DANALIM.DK  
PH. (+45) 56 64 00 70 - TECHNICAL SERVICE PH. (+45) 56 64 00 75**