

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Industrisealer 555

**Product no.**

55532

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Gluing.

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

Dana Lim A/S  
Københavnsvej 220  
DK-4600 Køge  
Denmark  
phone: +45 56 64 00 70  
fax: +45 56 64 00 90

**Contact person**

Product Safety Department

**E-mail**

info@danalim.dk

**SDS date**

2016-06-10

**SDS Version**

2.0

### 1.4. Emergency telephone number

Use your national or local emergency number  
See section 4 "First aid measures"

## SECTION 2: Hazards identification

### ▼ 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)**

-

**Signal word**

-

**Hazard statement(s)**

-

<b>Safety statement(s)</b>	General	-
	Prevention	-
	Response	-
	Storage	-
	Disposal	-

**Identity of the substances primarily responsible for the major health hazards**

-

### ▼ 2.3. Other hazards

-

### ▼ Additional labelling

Safety data sheet available on request. (EUH210)

### Additional warnings

-

### VOC

-

## SECTION 3: Composition/information on ingredients

### ▼ 3.1/3.2. Substances/Mixtures

NAME: Organosilan ester  
IDENTIFICATION NOS.: -  
CONTENT: 1-3%  
CLP CLASSIFICATION: Flam. Liq. 3, Acute Tox. 4  
H226, H332

NAME: Trimethoxyvinylsilane  
IDENTIFICATION NOS.: CAS-no: 2768-02-7 EC-no: 220-449-8 REACH-no: 01-2119513215-52-0003  
CONTENT: 1-3%  
CLP CLASSIFICATION: Flam. Liq. 3, Acute Tox. 4  
H226, H332

(\*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.

### Other informations

ATEmix(inhale, vapour) > 20  
ATEmix(inhale, dust/mist) > 20  
ATEmix(inhale, dust/mist) > 20000  
ATEmix(dermal) > 2000  
ATEmix(oral) > 2000

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.  
Contact a physician, if there is doubt about the injured person's condition, or the symptoms continuous.  
Never give the unconscious person water or alike.

#### Inhalation

Lead the person into fresh air and keep the person under watch.

#### Skin contact

Remove contaminated clothing and shoes at once. If there has been contact to some skin, wash is thoroughly with water and soap. Skin cleansing remedies can be used. DO NOT use solvents or a thinner.

#### Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30 °C), until irritation cease and for at least 15 min.

#### Ingestion

Give the person plenty to drink and keep the person under watch. If fainting: Contact a physician immediately and bring along this security datasheet or the label from the product. Do not induce vomiting, unless recommended by the physician. Lower the person's head, so that vomit does not run back into the mouth or throat.

#### Burns

Not applicable

### 4.2. Most important symptoms and effects, both acute and delayed

Non specific.

### 4.3. Indication of any immediate medical attention and special treatment needed

Non specific.

#### Information to medics

Bring this safety data sheet.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Recommendation: alcohol resistant foam, carbonic acid, powder, fog. Usage of a water beam is forbidden, since it can spread the fire.

#### ▼ 5.2. Special hazards arising from the substance or mixture

If the product gets exposed to high temperature, as in case of a fire, dangerous demolition products get created. These are: Carbon oxides. Some metal oxides. If exposed to decomposition products, a danger to one's health is at risk. Fire fighters should use proper protection gear. A closed container, which is exposed to fire, should be cooled with water. Do not allow the water from the fire extinction run into sewer systems and water streams.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No specific demands.

#### 6.2. Environmental precautions

No specific demands.

#### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. If possible, clean with cleaning supplies. Solvents should be avoided.

#### 6.4. Reference to other sections

See section 13 regarding handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### SECTION 7: Handling and storage

#### ▼ 7.1. Precautions for safe handling

Smoking, consumption of food and liquids as well as storage of tobacco, foods and liquids is not allowed in the room. See section on 'Exposure controls/personal protection' for information on personal protection.

#### ▼ 7.2. Conditions for safe storage, including any incompatibilities

Always store in the same container as the original material. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### ▼ Storage temperature

No data available.

#### 7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### ▼ OEL

Methanol (released in small quantities during vulcanisation) (EH40/2005)  
Long-term exposure limit (8-hour TWA reference period): 200 ppm | 266 mg/m<sup>3</sup>  
Short-term exposure limit (15-minute reference period): 250 ppm | 333 mg/m<sup>3</sup>  
Comments: Sk (Sk = Can be absorbed through skin. )

di-"isononyl" phthalate (EH40/2005)  
Long-term exposure limit (8-hour TWA reference period): - ppm | 5 mg/m<sup>3</sup>  
Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

##### ▼ DNEL / PNEC

DNEL (Methanol (released in small quantities during vulcanisation)): 260  
Exposure: Inhalation

#### 8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

##### General recommendations

▼ Smoking, consumption of food and liquids as well as storage of tobacco, foods and liquids, is not allowed in the room.

### Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

### Exposure limits

Trade users should encompass the rules of the work environment legislation on maximum concentrations of exposure. See work hygienic threshold limiting values below.

### Appropriate technical measures

Airborne gas and dust concentrations must be kept lowest possible and under the existing threshold limiting values (see below). In case the air streams in the work room is not sufficient, use for example an exhaust. Make sure there are visible signs for eye cleanser and shower.

### Hygiene measures

Wash hands before breaks and at the end of work.

### Measures to avoid environmental exposure

No specific demands.

### Individual protection measures, such as personal protective equipment



#### ▼ Generally

Use only CE marked protective equipment.

#### ▼ Respiratory Equipment

Not relevant if the room is well ventilated. If used in small and very badly ventilated rooms a respirator may be used.

#### Skin protection

No specific demands.

#### Hand protection

When applying the sealant with a caulking gun and when finishing with a joint nail, work can be carried out without gloves if skin contact is avoided. Recommended: Butyl/nitrile rubber. Breakthrough time: Follow the manufacturer's instructions

#### ▼ Eye protection

No specific demands.

## SECTION 9: Physical and chemical properties

### ▼ 9.1. Information on basic physical and chemical properties

Form	Pasta
Colour	White
Odour	No data available.
pH	No data available.
Viscosity	No data available.
Density (g/cm <sup>3</sup> )	1,46

### ▼ Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.

### ▼ Data on fire and explosion hazards

Flashpoint (°C)	No data available.
Ignition (°C)	No data available.
Self ignition (°C)	No data available.
Explosion limits (Vol %)	No data available.

### ▼ Solubility

Solubility in water	Insoluble
n-octanol/water coefficient	No data available.

### ▼ 9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7.

**10.3. Possibility of hazardous reactions**

Non specific.

▼ **10.4. Conditions to avoid**

Non specific.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Substance	Species	Test	Route of exposure	Result
Trimethoxyvinylsilane	Rabbit	LD50	Dermal	3200 mg/kg
Trimethoxyvinylsilane	Rat	LD50	Inhalation	16,8 mg/l/4h
Trimethoxyvinylsilane	Rat	LD50	Oral	7100 mg/kg
di-"isononyl" phthalate	Rabbit	LD50	Dermal	>3200 mg/kg
di-"isononyl" phthalate	Rat	LD50	Oral	>40000 mg/kg

▼ **Skin corrosion/irritation**

Data on substance: Trimethoxyvinylsilane

Organism: Rabbit

Duration of Exposure: 96 h

Result: Not irritating

**Serious eye damage/irritation**

Data on substance: Trimethoxyvinylsilane

Organism: Rabbit

Result: Irritating

**Respiratory or skin sensitisation**

No data available. Data on substance: Trimethoxyvinylsilane

Organism: Guinea pig

Result: Not sensitising

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

Non specific.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Substance	Species	Test	Duration	Result
Trimethoxyvinylsilane	Fish	LC50	96 h	191 mg/l
Trimethoxyvinylsilane	Daphnia	EC50	48 h	169 mg/l
Trimethoxyvinylsilane	Daphnia	NOEC	21 d	25 mg/l
Trimethoxyvinylsilane	Algae	NOEC	72 h	25 mg/l

**12.2. Persistence and degradability**

Substance	Biodegradability	Test	Result
Trimethoxyvinylsilane	No	No data available	No data available

**12.3. Bioaccumulative potential**

Substance	Potential bioaccumulation	LogPow	BCF
No data available.			

▼ **12.4. Mobility in soil**

di-"isononyl" phthalate: Log Koc= 7,04712, Calculated from LogPow (Low mobility potential.).

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

This product contains substances, which can give unwanted long term effects in a water environment, due to its poor decomposition.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

This product is not included in the regulation of dangerous waste.

▼ **Waste**

EWC code

08 04 10

**Specific labelling**

-

▼ **Contaminated packing**

No specific demands.

**SECTION 14: Transport information**

**14.1 – 14.4**

Non dangerous goods, referring to ADR and IMDG.

▼ **ADR/RID**

14.1. UN number -

14.2. UN proper shipping name -

14.3. Transport hazard class(es) -

14.4. Packing group -

Notes -

Tunnel restriction code -

▼ **IMDG**

UN-no. -

Proper Shipping Name -

Class -

PG\* -

EmS -

MP\*\* -

Hazardous constituent -

▼ **IATA/ICAO**

UN-no. -

Proper Shipping Name -

Class -

PG\* -

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

No data available

(\*) Packing group

(\*\*) Marine pollutant

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

-

#### **Demands for specific education**

-

#### **Additional information**

-

#### **Sources**

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). EC regulation 1907/2006 (REACH).

#### **15.2. Chemical safety assessment**

No

### **SECTION 16: Other information**

#### **▼ Full text of H-phrases as mentioned in section 3**

H226 - Flammable liquid and vapour.

H332 - Harmful if inhaled.

#### **The full text of identified uses as mentioned in section 1**

-

#### **Other symbols mentioned in section 2**

-

#### **Other**

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

#### **The safety data sheet is validated by**

Robert Pedersen

#### **Date of last essential change (First cipher in SDS version)**

2014-12-16

#### **Date of last minor change (Last cipher in SDS version)**

2014-12-16