

## SAFETY DATA SHEET

## NBS PU All Year Foam 583

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Trade name

NBS PU All Year Foam 583

## Unique formula identifier (UFI)

DFCY-CV4A-0Q82-8553

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture

1-component polyurethane foam ready for use

## Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**Dana Lim A/S**

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

## Contact person

Product Safety Department

## E-mail

info@danalim.dk

## Revision

08/02/2024

## SDS Version

5.0

## Date of previous version

08/02/2024 (4.0)

## 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2; H315, Causes skin irritation.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Eye Irrit. 2; H319, Causes serious eye irritation.

Acute Tox. 4; H332, Harmful if inhaled.

Resp. Sens. 1; H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT SE 3; H335, May cause respiratory irritation.

Carc. 2; H351, Suspected of causing cancer.

Lact. H362, May cause harm to breast-fed children.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 4; H413, May cause long lasting harmful effects to aquatic life.

## 2.2. Label elements

Hazard pictogram(s)



#### Signal word

Danger

#### Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)  
 Causes skin irritation. (H315)  
 May cause an allergic skin reaction. (H317)  
 Causes serious eye irritation. (H319)  
 Harmful if inhaled. (H332)  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled. (H334)  
 May cause respiratory irritation. (H335)  
 Suspected of causing cancer. (H351)  
 May cause harm to breast-fed children. (H362)  
 May cause damage to organs through prolonged or repeated exposure. (H373)  
 May cause long lasting harmful effects to aquatic life. (H413)

#### Precautionary statement(s)

##### General

If medical advice is needed, have product container or label at hand. (P101)  
 Keep out of reach of children. (P102)

##### ▼ Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)  
 Do not spray on an open flame or other ignition source. (P211)  
 Do not pierce or burn, even after use. (P251)  
 Use only outdoors or in a well-ventilated area. (P271)  
 Wear eye protection/protective gloves/protective clothing. (P280)

##### ▼ Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing. (P305+P351+P338)

##### ▼ Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

##### Disposal

Dispose of contents/container in accordance with local regulation  
 (P501)

#### Hazardous substances

Diphenyl methane diisocyanate, isomers and homologues  
 glycerol, propoxylated  
 Alkanes, C14-17, chloro

#### Additional labelling

EUH204, Contains isocyanates. May produce an allergic reaction.  
 Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.  
 Please use the attached protective gloves! Maximum period of use: 5 minutes. Throw away after use, do not re-use.  
 As from 24 August 2023 adequate training is required before industrial or professional use.  
 UFI: DFCY-CV4A-0Q82-8553

### 2.3. Other hazards

#### Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.  
 This product contains a vPvB and/or PBT substance:  
 Alkanes, C14-17, chloro (PBT)  
 This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Diphenyl methane diisocyanate, isomers and homologues	CAS No.: 9016-87-9 EC No.: 618-498-9 UK-REACH: Index No.:	40-60%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Acute Tox. 4, H332 Resp. Sens. 1, H334 (SCL: 0.10 %) STOT SE 3, H335 (SCL: 5.00 %) Carc. 2, H351 STOT RE 2, H373	[3]
glycerol, propoxylated	CAS No.: 25791-96-2 EC No.: 500-044-5 UK-REACH: Index No.:	15-25%	Acute Tox. 4, H302	
Alkanes, C14-17, chloro	CAS No.: 85535-85-9 EC No.: 287-477-0 UK-REACH: Index No.: 602-095-00-X	5-10%	EUH066 Lact. H362 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[5], [6]
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 UK-REACH: Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	
Propane-1,2-diol, propoxylated	CAS No.: 25322-69-4 EC No.: 500-039-8 UK-REACH: Index No.:	5-10%	Acute Tox. 4, H302	
Dimethyl ether	CAS No.: 115-10-6 EC No.: 204-065-8 UK-REACH: Index No.: 603-019-00-8	5-10%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	[1]
reaction products of phosphoryl trichloride and 2-methyloxirane	CAS No.: 1244733-77-4 EC No.: 807-935-0 UK-REACH: Index No.:	3-5%	Acute Tox. 4, H302	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: Index No.: 601-003-00-5	3-5%	Flam. Gas 1A, H220 Press. Gas (Comp.) H280	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[5] Substance is included in the Candidate List of substances of very high concern (SVHC).

[6] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

##### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.

##### Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

##### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

##### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

##### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.  
 Ensure adequate ventilation, especially in confined areas.  
 Avoid inhalation of vapours from spilled material.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

**6.4. Reference to other sections**

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

**7.2. Conditions for safe storage, including any incompatibilities**

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

**Recommended storage material**

Always store in containers of the same material as the original container.

**Storage temperature**

Dry, cool and well ventilated

**Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**7.3. Specific end use(s)**

This product should only be used for applications quoted in section 1.2.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

Dimethyl ether

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 766

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 958

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

**DNEL**

Alkanes, C14-17, chloro

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	28,75 mg/kg
Long term – Systemic effects - Workers	Dermal	47,9 mg/kg
Long term – Systemic effects - General population	Inhalation	2 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	6,7 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	0,58 mg/kg

Dimethyl ether

<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Systemic effects - General population	Inhalation	471 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	1894 mg/m <sup>3</sup>
<b>Diphenyl methane diisocyanate, isomers and homologues</b>		
<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Local effects - General population	Inhalation	0,025 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	0,05 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	0,05 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	0,1 mg/m <sup>3</sup>
<b>Propane-1,2-diol, propoxylated</b>		
<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Systemic effects - General population	Dermal	51 mg/kg
Long term – Systemic effects - Workers	Dermal	84 mg/kg
Long term – Systemic effects - General population	Oral	24 mg/kg

#### PNEC

##### Alkanes, C14-17, chloro

<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		0,001 mg/l
Freshwater sediment		13 mg/kg
Marine water		0,0002 mg/l
Marine water sediment		2,6 mg/kg
Sewage treatment plant		80 mg/l
Soil		11,9 mg/kg

##### Dimethyl ether

<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		0,155 mg/l
Freshwater sediment		0,681 mg/kg
Intermittent release		1,549 mg/l
Marine water		0,016 mg/l
Marine water sediment		0,069 mg/kg
Sewage treatment plant		160 mg/l
Soil		0,045 mg/kg

##### Diphenyl methane diisocyanate, isomers and homologues

<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		1 mg/L
Intermittent release		10 mg/L
Marine water		0,1 mg/L
Sewage treatment plant		1 mg/L
Soil		1 mg/kg

##### Propane-1,2-diol, propoxylated

<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		0,1 mg/l
Freshwater sediment		0,765 mg/kg
Intermittent release		1 mg/l

Marine water	0,01 mg/l
Marine water sediment	0,0765 mg/kg
Sewage treatment plant	100 mg/l
Soil	0,109 mg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Do not recirculate outlet air that contain the substances.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

## Individual protection measures, such as personal protective equipment


### Generally

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (e.g. type A1 according to standard EN 14387) is used. Use only UKCA marked protective equipment.


### Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
In case of intensive or longer exposure	Powered fresh air hose breathing apparatus				
In case of insufficient ventilation and short term use	Combination filter A2P2	Class 2	Brown/White	EN14387	


### Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	

### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.5	>480	EN374-2, EN388	

### Eye protection

Type	Standards	
Wear safety glasses with side shields.	EN166	

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Aerosol

#### Colour

Testing not relevant or not possible due to the nature of the product.

#### Odour / Odour threshold

Testing not relevant or not possible due to the nature of the product.

#### pH

Testing not relevant or not possible due to the nature of the product.

#### Density (g/cm<sup>3</sup>)

1 (20 °C)

#### Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

#### Particle characteristics

Testing not relevant or not possible due to the nature of the product.

#### Phase changes

##### Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

##### Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

##### Boiling point (°C)

-12

##### Vapour pressure

Testing not relevant or not possible due to the nature of the product.

##### Relative vapour density

Testing not relevant or not possible due to the nature of the product.

##### Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

#### Data on fire and explosion hazards

##### Flash point (°C)

-83

##### Flammability (°C)

The material is ignitable.

##### Auto-ignition temperature (°C)

460

##### Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

#### Solubility

##### Solubility in water

Insoluble

##### n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

##### Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

### 9.2. Other information

#### Other physical and chemical parameters

No data available.

#### Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability



The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid static electricity.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/substance	Diphenyl methane diisocyanate, isomers and homologues
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	Diphenyl methane diisocyanate, isomers and homologues
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	490 mg/m3, 4h ·

Harmful if inhaled.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Skin sensitisation

May cause an allergic skin reaction.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

May cause harm to breast-fed children.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

The product contains a substance / substances, which may cause harm to breast-fed children.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### Other information

Diphenyl methane diisocyanate, isomers and homologues has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance Diphenyl methane diisocyanate, isomers and homologues  
 Species: Daphnia  
 Duration: 24 hours  
 Test: EC50  
 Result: >1000 mg/l ·

Product/substance Diphenyl methane diisocyanate, isomers and homologues  
 Duration: 3 hours  
 Test: EC50  
 Result: >100 mg/l ·

Toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains a vPvB and/or PBT substance:  
 Alkanes, C14-17, chloro (PBT)

### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 7 - Carcinogenic

HP 13 - Sensitising

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### EWC code

16 05 04\* Gases in pressure containers (including halons) containing dangerous substances

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F	-	Yes	Limited quantities: 1 L Tunnel restriction

	<b>14.1 UN / ID</b>	<b>14.2 UN proper shipping name</b>	<b>14.3 Hazard class(es)</b>	<b>14.4 PG*</b>	<b>14.5 Env**</b>	<b>Other information:</b>
						code: 2 (D) See below for additional information.
IMDG	1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F	-	Yes	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F	-	Yes	See below for additional information.

\* Packing group

\*\* Environmental hazards

#### Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

#### SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

#### REACH, Annex XVII

Diphenyl methane diisocyanate, isomers and homologues is subject to restrictions, UK-REACH annex XVII (entry 74).

isobutane is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

Dimethyl ether is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

propane is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

#### Additional information

Tactile warning.

#### Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

[6] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.  
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.  
H220, Extremely flammable gas.  
H280, Contains gas under pressure; may explode if heated.  
H302, Harmful if swallowed.  
H315, Causes skin irritation.  
H317, May cause an allergic skin reaction.  
H319, Causes serious eye irritation.  
H332, Harmful if inhaled.  
H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335, May cause respiratory irritation.  
H351, Suspected of causing cancer.  
H362, May cause harm to breast-fed children.  
H373, May cause damage to organs through prolonged or repeated exposure.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

#### ▼ The safety data sheet is validated by

Product Safety Department

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en