

# How to use sealants during winter

In general Dana Lim A/S does not recommend to use sealants when the temperature is below +5 °C. At lower temperatures there is a risk of condensation, frost and ice on the surface of the joints, which can cause adhesion failure.

For all types of sealants the following applies, when sealing below +5 °C:

- There is a risk that the surface of the sealant gets dirty, as the time for skin formation is a lot longer.
- The curing is really slow and can almost stop completely. It will start again as soon as the temperature rises again.
- Because of the longer curing time, it is important to notice that it will take a lot longer time before the sealant can withstand mechanical effects

When sealing below +5 °C the following precautions has to be taken:

- The sealant should be stored at +15°C - +25°C.
- Dry and warm up the surfaces of the joint, and make sure they are totally dry.
- The sealant should be protected against dust, leaves, snow, mechanical effects etc. If necessary film mulching can be done.

If the above guidelines are followed, then most of Dana Lim's sealants can be used all year round.

For more information please see the product information on the particularly product.

*The information and data contained in this Product Information sheet are based on extensive laboratory testing and our practical experiences, and are meant for helping the user to find optimum working methods. As the conditions at the user are beyond our control, we make no warranties concerning the results, achieved by the products. The information's in this Product Information sheet are typical values, intended as a guideline. They should not be regarded as product specifications. Please also refer to our standard sales conditions and terms of delivery.*

**DANA LIM A/S - KØBENHAVNSVEJ 220 - DK-4600 KØGE –  
DENMARK – INFO@DANALIM.DK  
PH. (+45) 56 64 00 70 - TELEFAX (+45) 56 64 00 90 –  
TECHNICAL SERVICE PH. (+45) 56 64 00 75**

# HOW TO DO

